

屋内照明器具特性

品番 (品名)	LGB50805									
光源	LED2700_70_360 x1					360.0 lm				
管理番号	K0154654(0)DB1									
BZ分類	BZ5/0.7/BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 0%		反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
下方光束 100%	室指数	照明率 (X0.01)																ZCM			
保守率	良	0.69	0.6	58	46	38	33	57	45	38	33	54	44	38	33	52	43	37	33	31	
	中	0.67	0.8	68	57	49	44	67	56	49	43	64	55	48	43	61	53	48	43	41	
	否	0.63	1.0	75	64	57	51	73	63	56	51	70	62	56	51	68	60	55	50	48	
			1.25	81	71	64	59	79	70	64	59	76	69	63	58	73	67	62	58	55	
下方投影面積			1.5	85	76	70	64	83	75	69	64	80	73	68	64	77	72	67	63	61	
	等価発光面積		2.0	90	83	78	73	89	82	77	72	86	80	76	72	83	78	74	71	68	
取付高さ	器具間隔最大限		2.5	94	88	83	78	92	87	82	78	89	85	80	77	86	83	79	76	74	
	横方向 (A)	縦方向 (B)	3.0	96	91	86	83	95	90	86	82	92	88	84	81	89	86	83	80	77	
Hm	1.23Hm	1.23Hm	4.0	99	95	91	88	98	94	91	87	95	92	89	86	92	90	87	85	82	
			5.0	101	98	94	92	99	96	94	91	97	94	92	90	94	92	90	88	85	
			7.0	103	100	98	96	102	99	97	95	99	97	95	94	97	95	93	92	89	
			10.0	105	103	101	99	103	102	100	99	101	99	98	97	98	97	96	95	92	

