

屋内照明器具特性	
品番 (品名)	S P L 5 5 4 2 K
光源	LDA13L - G / Z100E / S / W ×5 1520.0 l m
管理番号	K0164509 (0) DB 1
B Z 分類	B Z 7

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	32 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	61 %	室指数	照明率 (X0.01)																Z C M	
保守率	良 中 否 0.67 0.63 0.56	0.6	45	33	26	20	42	31	24	20	36	28	22	18	31	24	19	16	12	
		0.8	52	41	33	28	49	39	32	26	43	34	28	24	37	30	25	21	16	
		1.0	58	47	39	33	54	44	37	32	47	39	33	29	41	34	30	26	20	
		1.25	63	53	45	39	59	50	43	37	51	44	38	34	45	39	34	30	24	
下方投影面積	c m ²	1.5	67	57	50	44	63	54	47	42	55	48	42	38	47	42	37	34	27	
		2.0	72	64	57	51	68	60	54	49	59	53	48	44	51	47	43	39	31	
取付高さ	器具間隔最大限		2.5	75	68	62	57	71	64	59	54	62	57	52	48	54	50	46	43	35
	横方向 (A)	縦方向 (B)	3.0	78	71	66	61	73	67	62	58	65	60	56	52	56	53	49	46	37
H m	1.06 H m	1.05 H m	4.0	81	76	71	66	76	72	67	63	68	64	60	57	59	56	53	51	41
			5.0	83	78	74	70	78	74	70	67	70	66	63	60	61	59	56	54	44
			7.0	86	82	79	75	81	78	75	72	72	69	67	65	64	62	60	58	47
			10.0	88	85	82	80	83	80	78	76	74	72	70	68	66	64	62	61	50

