

# 屋内照明器具特性

品番 (品名)	L G W 5 1 7 0 5 W				
光源	LLD6300V ×1                      1270.0 lm				
管理番号	K0165621(0)DB1				
BZ分類	BZ5				

器具効率	76%	天井	80%				70%				50%				30%				0%		
	上方光束		3%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		73%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m <sup>2</sup>		1.25	59	51	45	41	57	50	45	41	55	49	44	40	52	47	43	39	37	
	等価発光面積		c m <sup>2</sup>	1.5	62	55	49	45	60	54	49	45	58	52	48	44	55	50	46	43	41
取付高さ	器具間隔最大限		2.5	69	64	59	55	67	63	58	55	64	60	57	54	62	58	55	53	50	
	横方向 (A)	縦方向 (B)	3.0	71	66	62	59	69	65	61	58	66	63	60	57	64	61	58	56	53	
H m	1.25 H m	1.25 H m	4.0	73	69	66	63	72	68	65	62	69	66	63	61	66	64	62	60	57	
			5.0	75	72	69	66	73	70	68	65	71	68	66	64	68	66	64	62	60	
			7.0	77	74	72	70	75	73	71	69	72	71	69	67	70	68	67	66	63	
			10.0	78	76	74	73	77	75	73	72	74	73	71	70	72	70	69	68	65	

