

屋内照明器具特性	
品番 (品名)	LGW51714W
光源	LLD4300N ×1 930.0 lm
管理番号	K0165622(0)DB1
BZ分類	BZ5

器具効率	76%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	3%	床	10%				10%				10%				10%				0%	
下方光束	73%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	4.2	3.3	2.7	2.2	4.1	3.2	2.6	2.2	3.9	3.1	2.6	2.2	3.7	3.0	2.5	2.2	2.0
	中	0.6	0.8	4.9	4.0	3.4	3.0	4.8	4.0	3.4	3.0	4.6	3.8	3.3	2.9	4.3	3.7	3.2	2.9	2.7
	否	0.56	1.0	5.4	4.6	4.0	3.5	5.3	4.5	3.9	3.5	5.0	4.3	3.8	3.4	4.8	4.2	3.7	3.4	3.2
			1.25	5.9	5.1	4.5	4.1	5.7	5.0	4.5	4.0	5.4	4.8	4.4	4.0	5.2	4.7	4.2	3.9	3.7
下方投影面積		cm^2	1.5	6.2	5.5	4.9	4.5	6.0	5.4	4.9	4.4	5.7	5.2	4.7	4.4	5.5	5.0	4.6	4.3	4.1
等価発光面積		cm^2	2.0	6.6	6.0	5.5	5.1	6.4	5.9	5.4	5.0	6.1	5.7	5.3	5.0	5.9	5.5	5.1	4.9	4.6
取付高さ	器具間隔最大限		2.5	6.9	6.3	5.9	5.5	6.7	6.2	5.8	5.5	6.4	6.0	5.7	5.4	6.1	5.8	5.5	5.2	5.0
	横方向 (A)	縦方向 (B)	3.0	7.1	6.6	6.2	5.9	6.9	6.5	6.1	5.8	6.6	6.3	5.9	5.7	6.3	6.0	5.8	5.5	5.3
Hm	1.26Hm	1.26Hm	4.0	7.3	6.9	6.6	6.3	7.1	6.8	6.5	6.2	6.9	6.6	6.3	6.1	6.6	6.4	6.1	5.9	5.7
			5.0	7.4	7.1	6.8	6.6	7.3	7.0	6.7	6.5	7.0	6.8	6.6	6.4	6.8	6.6	6.4	6.2	5.9
			7.0	7.6	7.4	7.2	7.0	7.5	7.3	7.1	6.9	7.2	7.0	6.9	6.7	7.0	6.8	6.7	6.5	6.2
			10.0	7.8	7.6	7.4	7.3	7.6	7.5	7.3	7.2	7.4	7.2	7.1	7.0	7.1	7.0	6.9	6.8	6.5

