

# 屋内照明器具特性

品番 (品名)	LGB15475	
光源	LED2700_70_335 ×1	335.0 lm
管理番号	K0169190(0)DR1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 7%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	93%	床		10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM
保守率	良 0.63	0.6	0.6	83	77	73	70	82	76	72	70	80	75	72	69	78	74	71	69	67
	中 0.6	0.6	0.8	89	83	80	77	87	82	79	77	85	81	78	76	83	80	77	75	73
	否 0.56	1.0	92	87	84	81	91	87	83	81	88	85	82	80	86	83	81	79	77	
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	95	91	88	85	94	90	87	85	91	88	86	84	89	86	84	82	80	
		1.5	97	93	90	88	96	92	90	87	93	90	88	86	90	88	86	85	82	
取付高さ	器具間隔最大限		2.0	100	97	94	92	98	95	93	91	95	93	91	89	92	90	89	88	85
	横方向 (A)	縦方向 (B)	2.5	101	98	96	94	99	97	95	93	96	94	93	91	93	92	91	90	86
Hm	0.50Hm	0.50Hm	3.0	102	100	98	96	100	98	97	95	97	96	94	93	94	93	92	91	87
			4.0	103	102	100	99	102	100	99	97	98	97	96	95	95	94	93	92	89
			5.0	104	103	101	100	102	101	100	99	99	98	97	96	96	95	94	94	90
			7.0	105	104	103	102	103	102	101	100	100	99	98	98	96	96	95	95	91
			10.0	105	105	104	103	104	103	102	102	101	100	99	99	97	96	96	96	91

