

# 屋内照明器具特性

品番 (品名)	LGB16466														
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m														
管理番号	K0170955(0)DR1														
BZ分類	BZ5/0.9/BZ4														

器具効率	60%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 (X0.01)																ZCM	
下方光束	60%																			
保守率	良 中 否	0.67	0.6	3.4	2.7	2.2	1.9	3.3	2.6	2.2	1.8	3.2	2.6	2.1	1.8	3.0	2.5	2.1	1.8	1.7
		0.63	0.8	4.0	3.3	2.9	2.5	3.9	3.3	2.9	2.5	3.8	3.2	2.8	2.5	3.6	3.1	2.8	2.5	2.4
		0.56	1.0	4.5	3.8	3.4	3.0	4.4	3.8	3.4	3.0	4.2	3.7	3.3	3.0	4.0	3.6	3.3	3.0	2.9
			1.25	4.8	4.3	3.9	3.6	4.8	4.2	3.8	3.5	4.6	4.1	3.8	3.5	4.4	4.0	3.7	3.5	3.4
下方投影面積	c m <sup>2</sup>	1.5	5.1	4.6	4.2	3.9	5.0	4.6	4.2	3.9	4.8	4.4	4.1	3.9	4.7	4.3	4.1	3.8	3.7	
		2.0	5.5	5.0	4.7	4.4	5.4	5.0	4.7	4.4	5.2	4.9	4.6	4.4	5.0	4.8	4.5	4.3	4.2	
取付高さ	器具間隔最大限		2.5	5.7	5.3	5.0	4.8	5.6	5.3	5.0	4.8	5.4	5.1	4.9	4.7	5.2	5.0	4.8	4.7	
	横方向 (A)	縦方向 (B)	3.0	5.8	5.5	5.3	5.0	5.7	5.4	5.2	5.0	5.5	5.3	5.1	4.9	5.4	5.2	5.0	4.9	
H m	1.34 H m	1.34 H m	4.0	6.0	5.8	5.5	5.4	5.9	5.7	5.5	5.3	5.7	5.6	5.4	5.3	5.6	5.4	5.3	5.2	
			5.0	6.1	5.9	5.7	5.6	6.0	5.8	5.7	5.5	5.8	5.7	5.6	5.4	5.7	5.6	5.5	5.4	5.2
			7.0	6.2	6.1	5.9	5.8	6.1	6.0	5.9	5.8	6.0	5.9	5.8	5.7	5.8	5.7	5.7	5.6	
			10.0	6.3	6.2	6.1	6.0	6.2	6.1	6.0	6.0	6.1	6.0	5.9	5.8	5.9	5.9	5.8	5.7	

