

屋内照明器具特性	
品番 (品名)	LGB81011
光源	LLD2000LCB1 ×1 531.0 lm
管理番号	K0175306(0)DR1
BZ分類	BZ4

器具効率	86%	天井	80%				70%				50%				30%				0%		
	上方光束		86%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
					下方光束	0%	床	10%				10%				10%				10%	
室指数	照明率 (X0.01)																ZCM				
保守率	良	0.67	0.6	37	28	22	18	31	24	19	16	21	17	14	11	12	10	8	7	0	
	中	0.63	0.8	44	35	29	25	37	30	25	22	25	21	18	15	14	12	10	9	0	
	否	0.56	1.0	48	40	35	30	41	35	30	26	28	24	21	19	16	14	12	11	0	
			1.25	53	45	40	36	45	39	35	31	31	27	24	22	18	16	14	13	0	
下方投影面積			1.5	56	49	44	40	48	42	38	35	33	29	27	25	19	17	16	15	0	
	等価発光面積		2.0	60	54	50	46	51	47	43	40	35	33	30	28	20	19	18	17	0	
取付高さ	器具間隔最大限		2.5	63	58	54	50	54	50	47	44	37	35	33	31	21	20	19	18	0	
	横方向 (A)	縦方向 (B)	3.0	64	60	57	54	55	52	49	47	38	36	34	33	22	21	20	19	0	
Hm	1.18Hm	1.35Hm	4.0	67	63	61	58	58	55	52	50	40	38	37	35	23	22	22	21	0	
			5.0	68	65	63	61	59	57	55	53	41	39	38	37	24	23	22	22	0	
			7.0	70	68	66	64	60	59	57	56	42	41	40	39	25	24	24	23	0	
			10.0	71	70	68	67	61	60	59	58	43	42	41	41	25	25	24	24	0	

