

# 屋内照明器具特性

品番 (品名)	LGB81613														
光源	LDA4 WW- H- E17 / E / S / W / 2 × 1										440.0 1 m				
管理番号	K0164136 ( 1 ) D 1														
BZ分類	BZ4 / 0.7 / BZ3														

器具効率	53 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	2 %	室指数																		
下方光束	51 %	照明率 ( X0.01 )																		
		ZCM																		
保守率	良 中 否	0.67	0.6	3.2	2.6	2.2	1.9	3.1	2.6	2.2	1.9	3.0	2.5	2.2	1.9	2.8	2.4	2.1	1.9	1.8
		0.63	0.8	3.8	3.2	2.9	2.6	3.7	3.2	2.8	2.6	3.5	3.1	2.8	2.5	3.4	3.0	2.7	2.5	2.4
		0.56	1.0	4.1	3.6	3.3	3.0	4.0	3.6	3.3	3.0	3.9	3.5	3.2	3.0	3.7	3.4	3.1	2.9	2.8
			1.25	4.4	4.0	3.7	3.4	4.3	3.9	3.6	3.4	4.2	3.8	3.6	3.4	4.0	3.7	3.5	3.3	3.2
下方投影面積	c m <sup>2</sup>	1.5	4.6	4.2	3.9	3.7	4.5	4.2	3.9	3.7	4.4	4.1	3.8	3.6	4.2	3.9	3.7	3.6	3.4	
		2.0	4.9	4.6	4.3	4.1	4.8	4.5	4.3	4.1	4.6	4.4	4.2	4.0	4.5	4.3	4.1	3.9	3.8	
取付高さ	器具間隔最大限		2.5	5.0	4.8	4.6	4.4	5.0	4.7	4.5	4.3	4.8	4.6	4.4	4.3	4.6	4.4	4.3	4.2	4.0
	横方向 (A)	縦方向 (B)	3.0	5.2	4.9	4.7	4.6	5.1	4.9	4.7	4.5	4.9	4.7	4.6	4.4	4.7	4.6	4.5	4.3	4.2
H m	1.38 H m	1.38 H m	4.0	5.3	5.1	5.0	4.8	5.2	5.0	4.9	4.8	5.0	4.9	4.8	4.7	4.9	4.7	4.6	4.6	4.4
			5.0	5.4	5.2	5.1	5.0	5.3	5.1	5.0	4.9	5.1	5.0	4.9	4.8	4.9	4.8	4.8	4.7	4.5
			7.0	5.5	5.3	5.2	5.2	5.4	5.3	5.2	5.1	5.2	5.1	5.0	5.0	5.0	5.0	4.9	4.8	4.6
			10.0	5.5	5.4	5.4	5.3	5.4	5.4	5.3	5.2	5.3	5.2	5.2	5.1	5.1	5.1	5.0	5.0	4.8

