

屋内照明器具特性

品番 (品名)	LGB81611	
光源	LDA3L-E17/C/W x1	280.0 lm
管理番号	K0169956(1)DR1	
BZ分類	BZ5/0.7/BZ4/6.0/BZ5	

器具効率	47%	天井	80%				70%				50%				30%				0%		
	上方光束		5%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		42%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	2.7	2.1	1.8	1.5	2.6	2.1	1.7	1.5	2.4	2.0	1.7	1.5	2.3	1.9	1.6	1.4	1.3	
	中	0.63	0.8	3.1	2.6	2.3	2.0	3.0	2.6	2.2	2.0	2.9	2.5	2.2	1.9	2.7	2.4	2.1	1.9	1.8	
	否	0.56	1.0	3.4	3.0	2.6	2.4	3.3	2.9	2.6	2.4	3.2	2.8	2.5	2.3	3.0	2.7	2.4	2.2	2.1	
			0.56	1.25	3.7	3.3	3.0	2.7	3.6	3.2	2.9	2.7	3.4	3.1	2.8	2.6	3.2	3.0	2.7	2.6	2.4
下方投影面積	c m ²		1.5	3.9	3.5	3.2	3.0	3.8	3.5	3.2	3.0	3.6	3.3	3.1	2.9	3.4	3.2	3.0	2.8	2.6	
	等価発光面積		c m ²	2.0	4.2	3.8	3.6	3.4	4.0	3.8	3.5	3.3	3.8	3.6	3.4	3.2	3.6	3.4	3.3	3.1	2.9
取付高さ	器具間隔最大限		2.5	4.3	4.0	3.8	3.6	4.2	3.9	3.7	3.6	4.0	3.8	3.6	3.4	3.8	3.6	3.5	3.3	3.1	
	横方向 (A)	縦方向 (B)	3.0	4.4	4.2	4.0	3.8	4.3	4.1	3.9	3.7	4.1	3.9	3.7	3.6	3.9	3.7	3.6	3.5	3.3	
H m	0.76 H m	0.78 H m	4.0	4.5	4.3	4.2	4.0	4.4	4.3	4.1	4.0	4.2	4.1	3.9	3.8	4.0	3.9	3.8	3.7	3.5	
			5.0	4.6	4.5	4.3	4.2	4.5	4.4	4.2	4.1	4.3	4.2	4.1	4.0	4.1	4.0	3.9	3.8	3.6	
			7.0	4.7	4.6	4.5	4.4	4.6	4.5	4.4	4.3	4.4	4.3	4.2	4.1	4.2	4.1	4.0	4.0	3.7	
			10.0	4.8	4.7	4.6	4.5	4.7	4.6	4.5	4.4	4.5	4.4	4.3	4.3	4.3	4.2	4.2	4.1	3.9	

