

屋内照明器具特性	
品番 (品名)	LGB10085
光源	LED3500_70_432 x1 432.0 lm
管理番号	K0164288(0)DB1
BZ分類	BZ3/1.8/BZ4/8.5/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	12%	床	10%				10%				10%				10%				0%	
下方光束	88%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	61	50	44	39	59	49	43	38	56	48	42	38	53	46	41	37	34
	中	0.63	0.8	70	61	54	49	68	59	53	48	65	57	51	47	61	55	50	46	43
	否	0.56	1.0	76	67	61	56	74	66	60	55	70	63	58	54	66	60	56	52	49
			1.25	81	73	67	62	79	72	66	61	75	68	63	60	71	65	61	58	54
下方投影面積		cm ²	1.5	85	77	71	67	82	76	70	66	78	72	68	64	74	69	65	62	58
等価発光面積		cm ²	2.0	89	83	78	74	87	81	76	72	82	77	73	70	78	74	70	68	63
取付高さ	器具間隔最大限		2.5	92	87	82	78	90	85	80	77	85	81	77	74	80	77	74	71	67
	横方向 (A)	縦方向 (B)	3.0	94	89	85	82	92	87	83	80	87	83	80	77	82	79	77	74	69
Hm	1.24Hm	1.24Hm	4.0	97	93	89	86	94	91	88	85	89	86	84	81	85	82	80	78	73
			5.0	98	95	92	89	96	93	90	88	91	88	86	84	86	84	82	81	75
			7.0	100	98	95	93	98	95	93	91	93	91	89	88	88	87	85	84	78
			10.0	102	100	98	96	99	98	96	94	94	93	92	90	90	89	87	86	80

