

屋内照明器具特性

品番 (品名)	LGB81000														
光源	LLD2000CU1 x1 566.0 lm														
管理番号	K0178913(0)DR1														
BZ分類	BZ9/0.7/BZ8														

器具効率	92%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	41% 51%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.63 0.6 0.56	0.6	4.2	3.0	2.2	1.7	3.8	2.8	2.1	1.6	3.2	2.4	1.8	1.4	2.6	2.0	1.5	1.2	0.7		
		0.8	4.9	3.8	3.0	2.4	4.5	3.5	2.8	2.3	3.8	3.0	2.4	2.0	3.1	2.5	2.0	1.7	1.1		
		1.0	5.5	4.4	3.6	3.0	5.0	4.1	3.4	2.8	4.2	3.5	2.9	2.4	3.5	2.9	2.4	2.0	1.4		
		1.25	6.0	5.0	4.2	3.6	5.5	4.6	3.9	3.4	4.6	3.9	3.4	2.9	3.8	3.3	2.8	2.5	1.7		
下方投影面積 等価発光面積	c m ² c m ²	1.5	6.4	5.4	4.7	4.1	5.9	5.0	4.4	3.8	5.0	4.3	3.7	3.3	4.1	3.6	3.2	2.8	1.9		
		2.0	6.9	6.1	5.4	4.8	6.4	5.6	5.0	4.5	5.4	4.8	4.3	3.9	4.5	4.0	3.7	3.3	2.4		
取付 高さ	器具間隔最大限		2.5	7.2	6.5	5.9	5.3	6.7	6.0	5.5	5.0	5.7	5.2	4.7	4.3	4.8	4.4	4.0	3.7	2.7	
	横方向 (A) H m	縦方向 (B) H m	3.0	7.5	6.8	6.2	5.7	6.9	6.4	5.8	5.4	5.9	5.5	5.0	4.7	5.0	4.6	4.3	4.0	2.9	
			4.0	7.8	7.3	6.8	6.3	7.3	6.8	6.3	5.9	6.2	5.8	5.5	5.2	5.2	4.9	4.7	4.4	3.3	
			5.0	8.0	7.5	7.1	6.7	7.5	7.0	6.7	6.3	6.4	6.1	5.8	5.5	5.4	5.2	4.9	4.7	3.5	
			7.0	8.3	7.9	7.6	7.2	7.7	7.4	7.1	6.8	6.7	6.4	6.2	5.9	5.7	5.5	5.3	5.1	3.8	
			10.0	8.5	8.2	7.9	7.7	7.9	7.7	7.4	7.2	6.9	6.7	6.5	6.3	5.9	5.7	5.5	5.4	4.1	

