

屋内照明器具特性

品番 (品名)	XLGB81900															
光源	LED5000_70_360 x1 360.0 lm															
管理番号	K0171432(0)DB1															
BZ分類	BZ9/0.9/BZ8															

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	50%																			
下方光束	50%																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否	0.63	0.6	4.4	3.2	2.4	1.8	4.0	2.9	2.2	1.7	3.3	2.4	1.8	1.4	2.6	2.0	1.5	1.1	0.6
		0.6	0.8	5.3	4.0	3.2	2.6	4.8	3.7	3.0	2.4	3.9	3.1	2.5	2.0	3.1	2.5	2.0	1.6	0.9
			1.0	5.9	4.7	3.8	3.2	5.4	4.3	3.5	3.0	4.4	3.6	3.0	2.5	3.5	2.9	2.4	2.0	1.2
		0.56	1.25	6.4	5.3	4.5	3.8	5.9	4.9	4.1	3.5	4.8	4.1	3.5	3.0	3.9	3.3	2.8	2.4	1.5
下方投影面積	c m ²	1.5	6.8	5.8	5.0	4.3	6.2	5.3	4.6	4.0	5.1	4.4	3.9	3.4	4.1	3.6	3.2	2.8	1.8	
		2.0	7.4	6.5	5.7	5.1	6.8	6.0	5.3	4.8	5.6	5.0	4.5	4.0	4.5	4.1	3.7	3.3	2.2	
取付高さ	器具間隔最大限		2.5	7.8	7.0	6.3	5.7	7.1	6.4	5.8	5.3	5.9	5.4	4.9	4.5	4.8	4.4	4.0	3.7	2.5
	横方向 (A)	縦方向 (B)	3.0	8.0	7.3	6.7	6.2	7.4	6.7	6.2	5.7	6.2	5.7	5.2	4.8	5.0	4.6	4.3	4.0	2.7
H m	1.59 H m	2.09 H m	4.0	8.4	7.8	7.2	6.8	7.7	7.2	6.7	6.3	6.5	6.1	5.7	5.4	5.3	5.0	4.7	4.4	3.0
			5.0	8.6	8.1	7.6	7.2	7.9	7.5	7.1	6.7	6.7	6.3	6.0	5.7	5.5	5.2	5.0	4.7	3.3
			7.0	8.9	8.5	8.1	7.8	8.2	7.9	7.5	7.2	6.9	6.7	6.4	6.2	5.7	5.5	5.3	5.1	3.6
			10.0	9.1	8.8	8.5	8.2	8.4	8.2	7.9	7.7	7.2	6.9	6.7	6.5	6.0	5.8	5.6	5.5	3.9

