

# 屋内照明器具特性

品番 (品名)	LGB10718K									
光源	LED6200_70_422 x1					422.0 lm				
管理番号	K0153703(0)DB1									
BZ分類	BZ4/0.7/BZ3/1.8/BZ4/8.5/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	7%	床	10%				10%				10%				10%				0%	
下方光束	93%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	60	49	42	37	58	48	41	36	56	46	40	36	53	45	40	35	33
	中	0.63	0.8	70	60	53	48	69	59	52	48	65	57	51	47	62	55	50	46	44
	否	0.56	1.0	77	67	61	56	75	66	60	55	71	64	59	54	68	62	57	53	51
			1.25	82	74	67	62	80	72	66	62	76	70	65	61	73	68	63	60	57
下方投影面積			1.5	86	78	72	67	84	77	71	67	80	74	69	65	76	71	67	64	61
			2.0	90	84	79	74	88	82	77	73	84	79	75	72	81	77	73	70	67
取付高さ	器具間隔最大限		2.5	93	88	83	79	91	86	82	78	87	83	79	76	84	80	77	74	70
	横方向 (A)	縦方向 (B)	3.0	95	90	86	82	93	89	85	81	89	85	82	79	86	82	80	77	73
Hm	1.32Hm	1.32Hm	4.0	98	94	90	87	96	92	89	86	92	89	86	84	88	86	83	81	77
			5.0	99	96	93	90	97	94	92	89	93	91	89	86	90	88	86	84	80
			7.0	101	99	96	94	99	97	95	93	95	93	92	90	92	90	89	87	83
			10.0	103	101	99	97	101	99	97	96	97	96	94	93	93	92	91	90	85

