

# 屋内照明器具特性

|         |                   |  |          |  |  |
|---------|-------------------|--|----------|--|--|
| 品番 (品名) | XLGB81915         |  |          |  |  |
| 光源      | LED5000_70_190 x1 |  | 190.0 lm |  |  |
| 管理番号    | K0169181(1)DR1    |  |          |  |  |
| BZ分類    | BZ5/0.7/BZ4       |  |          |  |  |

|        |                  |          |                  |     |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|--------|------------------|----------|------------------|-----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 100%             | 天井       | 80%              |     |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|        |                  | 壁        | 70               | 50  | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 50%              | 床        | 10%              |     |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 50%              | 室指数      | 照明率 ( X0.01)     |     |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良                | 0.63     | 0.6              | 51  | 40 | 32 | 27  | 47 | 37 | 31 | 26  | 40 | 32 | 27 | 23  | 33 | 27 | 23 | 20  | 15 |
|        | 中                | 0.6      | 0.8              | 60  | 50 | 42 | 37  | 56 | 46 | 40 | 35  | 47 | 40 | 35 | 32  | 40 | 35 | 31 | 28  | 21 |
|        | 否                | 0.56     | 1.0              | 66  | 57 | 50 | 45  | 61 | 53 | 47 | 42  | 52 | 46 | 41 | 38  | 44 | 39 | 36 | 33  | 25 |
|        |                  |          | 1.25             | 72  | 63 | 57 | 52  | 67 | 59 | 53 | 49  | 57 | 51 | 47 | 43  | 48 | 44 | 41 | 38  | 29 |
| 下方投影面積 | c m <sup>2</sup> |          | 1.5              | 76  | 68 | 62 | 57  | 70 | 64 | 58 | 54  | 60 | 55 | 51 | 48  | 51 | 47 | 44 | 41  | 32 |
|        | 等価発光面積           |          | c m <sup>2</sup> | 2.0 | 81 | 74 | 69  | 65 | 75 | 70 | 65  | 61 | 64 | 60 | 57  | 54 | 54 | 51 | 49  | 47 |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 84  | 79 | 74 | 70  | 78 | 73 | 69 | 66  | 67 | 63 | 60 | 58  | 57 | 54 | 52 | 50  | 38 |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 86  | 81 | 77 | 74  | 80 | 76 | 72 | 69  | 69 | 66 | 63 | 61  | 58 | 56 | 54 | 52  | 40 |
| H m    | 0.00 H m         | 1.64 H m | 4.0              | 89  | 85 | 82 | 79  | 83 | 80 | 77 | 74  | 71 | 69 | 67 | 65  | 60 | 58 | 57 | 56  | 42 |
|        |                  |          | 5.0              | 91  | 88 | 85 | 82  | 84 | 82 | 79 | 77  | 73 | 71 | 69 | 67  | 61 | 60 | 59 | 58  | 43 |
|        |                  |          | 7.0              | 93  | 90 | 88 | 86  | 86 | 84 | 82 | 81  | 74 | 73 | 71 | 70  | 63 | 62 | 61 | 60  | 45 |
|        |                  |          | 10.0             | 94  | 92 | 91 | 89  | 88 | 86 | 85 | 84  | 76 | 74 | 73 | 73  | 64 | 63 | 63 | 62  | 46 |

