

屋内照明器具特性	
品番(品名)	LGB81002
光源	LLD2000CU1 x1 566.0lm
管理番号	K0178752(0)DR1
BZ分類	BZ4/0.9/BZ3

器具効率	32%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	10%	床	10%				10%				10%				10%				0%	
下方光束	22%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	17	14	12	10	16	13	11	10	15	12	10	9	13	11	10	9	7
	中	0.6	0.8	20	17	15	13	19	16	14	13	17	15	13	12	16	14	12	11	10
	否	0.56	1.0	22	19	17	16	21	18	17	15	19	17	15	14	17	15	14	13	11
			1.25	24	21	19	18	23	20	19	17	21	19	17	16	19	17	16	15	13
下方投影面積	c m ²	1.5	25	23	21	19	24	22	20	19	22	20	19	17	19	18	17	16	14	
		2.0	27	25	23	22	26	24	22	21	23	22	21	20	21	20	19	18	16	
取付高さ	器具間隔最大限		2.5	28	26	25	23	27	25	24	23	24	23	22	21	22	21	20	19	17
	横方向(A)	縦方向(B)	3.0	29	27	26	25	27	26	25	24	25	24	23	22	22	21	21	20	17
H m	1.15 H m	1.25 H m	4.0	29	28	27	26	28	27	26	25	25	25	24	23	23	22	22	21	18
			5.0	30	29	28	27	29	28	27	26	26	25	25	24	23	23	22	22	19
			7.0	31	30	29	29	29	28	28	27	26	26	26	25	24	24	23	23	20
			10.0	31	30	30	30	30	29	29	28	27	27	26	26	24	24	24	24	20

