

屋内照明器具特性	
品番 (品名)	L G D 3 2 0 1 N
光源	LED5000_70_830 ×1 830.0 l m
管理番号	K0148420 (0) DB 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6	5 8	4 6	3 9	3 4	5 7	4 6	3 9	3 3	5 5	4 5	3 8	3 3	5 3	4 4	3 8	3 3	3 1	
			0 . 8	6 8	5 7	5 0	4 4	6 7	5 7	4 9	4 4	6 4	5 5	4 9	4 4	6 2	5 4	4 8	4 4	4 2	
			1 . 0	7 5	6 5	5 7	5 2	7 4	6 4	5 7	5 2	7 1	6 2	5 6	5 1	6 8	6 1	5 5	5 1	4 9	
			1 . 2 5	8 1	7 2	6 5	6 0	7 9	7 1	6 5	5 9	7 7	6 9	6 4	5 9	7 4	6 8	6 3	5 9	5 6	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 5	7 7	7 1	6 5	8 4	7 6	7 0	6 5	8 1	7 4	6 9	6 5	7 8	7 2	6 8	6 4	6 2	
			2 . 0	9 1	8 4	7 9	7 4	8 9	8 3	7 8	7 4	8 6	8 1	7 7	7 3	8 4	7 9	7 5	7 2	7 0	
			2 . 5	9 4	8 9	8 4	8 0	9 3	8 7	8 3	7 9	9 0	8 5	8 2	7 8	8 7	8 3	8 0	7 7	7 5	
			3 . 0	9 7	9 2	8 7	8 4	9 5	9 1	8 7	8 3	9 2	8 9	8 5	8 2	9 0	8 7	8 4	8 1	7 9	
H m	1 . 2 2 H m	1 . 2 2 H m	4 . 0	1 0 0	9 6	9 2	8 9	9 8	9 5	9 1	8 9	9 5	9 2	9 0	8 7	9 3	9 0	8 8	8 6	8 3	
			5 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	8 9	8 6	
			7 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	9 9	9 8	9 6	9 4	9 7	9 5	9 4	9 3	9 0	
			1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 7	9 6	9 3	

