

屋内照明器具特性

品番 (品名)	XLGB81910									
光源	LED5000_70_215 x1					215.0 lm				
管理番号	K0169180(1)DR1									
BZ分類	BZ5/0.7/BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	50%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	50%																																																						
保守率	良 中 否 0.63 0.6 0.56	0.6	50	39	32	27	46	36	30	25	39	32	26	23	33	27	23	20	15																																				
		0.8	60	49	42	37	55	46	39	35	47	40	35	31	39	34	30	27	20																																				
		1.0	66	56	49	44	61	52	46	42	52	45	41	37	43	39	35	32	24																																				
		1.25	71	63	56	51	66	59	53	48	56	51	46	43	47	43	40	37	28																																				
下方投影面積	c m ²	1.5	75	67	61	56	70	63	57	53	59	54	50	47	50	46	43	41	31																																				
		2.0	80	74	69	64	75	69	64	60	64	60	56	53	54	51	48	46	35																																				
等価発光面積	c m ²	2.5	84	78	73	69	78	73	69	65	66	63	60	57	56	53	51	49	37																																				
		3.0	86	81	77	73	80	76	72	69	68	65	63	60	58	55	53	52	39																																				
取付高さ	器具間隔最大限		4.0	89	85	81	78	83	79	76	74	71	68	66	64	60	58	56	41																																				
	横方向 (A)	縦方向 (B)	5.0	90	87	84	82	84	81	79	77	72	70	68	67	61	60	58	43																																				
H m	0.00 H m	1.67 H m	7.0	92	90	88	86	86	84	82	80	74	72	71	70	62	61	60	44																																				
			10.0	94	92	91	89	87	86	85	83	75	74	73	72	64	63	62	46																																				

