

屋内照明器具特性

品番 (品名)	LGB81005																
光源	LLD4000LCB1 ×1 845.0 lm																
管理番号	K0176419(0)DR1																
BZ分類	BZ9/0.9/BZ8																

器具効率	81%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	41% 40%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.63 0.6 0.56	0.6	36	26	19	15	33	24	18	14	27	20	15	11	21	16	12	9	5		
		0.8	43	33	26	21	39	30	24	19	32	25	20	16	25	20	16	13	8		
		1.0	47	38	31	26	43	35	29	24	35	29	24	20	28	23	19	16	10		
		1.25	52	43	36	31	47	40	33	29	39	33	28	24	31	27	23	20	12		
下方投影面積 等価発光面積	c m ² c m ²	1.5	55	47	40	35	51	43	37	33	42	36	31	27	33	29	25	22	14		
		2.0	60	52	47	42	55	48	43	39	45	40	36	33	37	33	30	27	17		
取付 高さ	器具間隔最大限		2.5	63	56	51	46	58	52	47	43	48	44	40	36	39	36	33	20		
	横方向 (A) H m	縦方向 (B) H m	3.0	65	59	54	50	60	55	50	46	50	46	42	39	41	38	35	22		
			4.0	68	63	59	55	63	58	54	51	52	49	46	43	43	40	38	25		
			5.0	70	65	62	58	64	61	57	54	54	51	49	46	45	42	40	27		
			7.0	72	69	66	63	66	64	61	58	56	54	52	50	47	45	43	29		
			10.0	74	71	69	67	68	66	64	62	58	56	55	53	48	47	46	31		

