

屋内照明器具特性

品番 (品名)	LGB81006				
光源	LLD4000LCB1 ×1 845.0 lm				
管理番号	K0176414 (0) DR1				
BZ分類	BZ5/0.7/BZ4				

器具効率	44%	天井	80%				70%				50%				30%				0%			
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
				床	10%				10%				10%				10%				0%	
上方光束	22%	室指数																				
下方光束	22%	照明率 (X0.01)																				
		ZCM																				
保守率	良中否	0.63	0.6	0.56	0.6	2.2	1.7	1.4	1.2	2.0	1.6	1.3	1.1	1.7	1.4	1.1	1.0	1.4	1.2	1.0	0.9	0.6
		0.6	0.8	2.6	2.1	1.8	1.6	2.4	2.0	1.7	1.5	2.0	1.7	1.5	1.3	1.7	1.5	1.3	1.2	0.9		
		1.0	2.9	2.4	2.1	1.9	2.7	2.3	2.0	1.8	2.3	2.0	1.8	1.6	1.9	1.7	1.5	1.4	1.1			
		0.56	1.25	3.1	2.7	2.4	2.2	2.9	2.5	2.3	2.1	2.5	2.2	2.0	1.8	2.1	1.9	1.7	1.6	1.2		
下方投影面積	cm ²	1.5	3.3	2.9	2.7	2.4	3.0	2.7	2.5	2.3	2.6	2.4	2.2	2.0	2.2	2.0	1.9	1.8	1.3			
		2.0	3.5	3.2	3.0	2.8	3.3	3.0	2.8	2.6	2.8	2.6	2.4	2.3	2.2	2.1	2.0	1.5				
		2.5	3.6	3.4	3.2	3.0	3.4	3.2	3.0	2.8	2.9	2.7	2.6	2.5	2.4	2.3	2.2	1.6				
取付高さ	器具間隔最大限		H _m	0.00H _m	1.67H _m	3.0	3.7	3.5	3.3	3.2	3.5	3.3	3.1	3.0	3.0	2.8	2.7	2.6	2.5	2.4	2.3	1.7
	4.0	3.9				3.7	3.5	3.4	3.6	3.5	3.3	3.2	3.1	3.0	2.9	2.8	2.6	2.5	2.5	2.4	1.8	
						5.0	3.9	3.8	3.7	3.6	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.7	2.6	2.5	1.9
						7.0	4.0	3.9	3.8	3.7	3.8	3.7	3.6	3.5	3.2	3.2	3.1	3.0	2.7	2.7	2.6	2.0
						10.0	4.1	4.0	3.9	3.9	3.8	3.8	3.7	3.6	3.3	3.2	3.2	3.2	2.8	2.8	2.7	2.0

