

屋内照明器具特性	
品番 (品名)	L G D 3 4 0 1 V
光源	LED3500_70_585 ×1 585.0 l m
管理番号	K0151185 (0) DB 1
B Z 分類	BZ3 / 1.1 / BZ2

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束				1 0 0 %																				
保守率		良 中 否	0 . 6 7	0 . 6	6 4	5 3	4 6	4 1	6 2	5 2	4 6	4 1	6 0	5 1	4 5	4 1	5 8	5 0	4 5	4 1	3 9			
			0 . 6 3	0 . 8	7 4	6 5	5 8	5 4	7 3	6 4	5 8	5 3	7 1	6 3	5 7	5 3	6 9	6 2	5 7	5 3	5 1			
			0 . 5 6	1 . 0	8 1	7 3	6 7	6 2	8 0	7 2	6 6	6 2	7 7	7 1	6 5	6 1	7 5	6 9	6 5	6 1	5 9			
				1 . 2 5	8 7	7 9	7 4	7 0	8 5	7 9	7 3	6 9	8 3	7 7	7 2	6 9	8 1	7 6	7 2	6 8	6 6			
下方投影面積		c m ²	1 . 5	9 0	8 4	7 9	7 5	8 9	8 3	7 8	7 4	8 6	8 1	7 7	7 4	8 4	8 0	7 6	7 3	7 1				
等価発光面積			c m ²	2 . 0	9 5	9 0	8 5	8 2	9 4	8 9	8 5	8 1	9 1	8 7	8 4	8 1	8 9	8 5	8 2	8 0	7 8			
取付高さ	器具間隔最大限			2 . 5	9 8	9 3	9 0	8 7	9 6	9 2	8 9	8 6	9 4	9 1	8 8	8 5	9 2	8 9	8 6	8 4	8 2			
		横方向 (A)		縦方向 (B)		3 . 0	1 0 0	9 6	9 3	9 0	9 8	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 3	9 1	8 9	8 7	8 5	
H m	1 . 1 9 H m	1 . 2 0 H m	4 . 0	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 1	8 8				
			5 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	9 9	9 8	9 6	9 4	9 7	9 6	9 4	9 3	9 0				
			7 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 7	9 6	9 3				
			1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 8	9 5				

