

屋内照明器具特性

品番 (品名)	LGB81008															
光源	LLD4000LCB1 ×1 845.0 1m															
管理番号	K0176416(0)DR1															
BZ分類	BZ5/0.7/BZ4															

器具効率	38%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	19%	床	10%				10%				10%				10%				0%	
下方光束	19%	室指数	照明率 (X0.01) ZCM																	
保守率	良 0.63 中 0.6 否 0.56	0.6	19	15	12	10	18	14	12	10	15	12	10	9	13	10	9	8	6	
		0.8	23	19	16	14	21	18	15	13	18	15	13	12	15	13	12	10	8	
		1.0	25	22	19	17	23	20	18	16	20	17	16	14	17	15	14	12	9	
		1.25	27	24	22	20	25	23	20	19	22	19	18	16	18	17	15	14	11	
下方投影面積	c m ²	1.5	29	26	24	22	27	24	22	20	23	21	19	18	19	18	17	16	12	
		2.0	31	28	26	25	29	26	25	23	24	23	22	20	21	19	18	18	13	
取付高さ	器具間隔最大限		2.5	32	30	28	27	30	28	26	25	25	24	23	22	21	21	20	19	14
	横方向 (A)	縦方向 (B)	3.0	33	31	29	28	31	29	28	26	26	25	24	23	22	21	21	20	15
H m	0.00 H m	1.64 H m	4.0	34	33	31	30	32	30	29	28	27	26	25	23	22	22	21	21	16
			5.0	35	33	32	31	32	31	30	29	28	27	26	26	23	23	22	22	16
			7.0	35	34	34	33	33	32	31	31	28	28	27	27	24	24	23	23	17
			10.0	36	35	35	34	33	33	32	32	29	28	28	28	24	24	24	24	18

