

# 屋内照明器具特性

品番 (品名)	LGB81010	
光源	LLD4000LCS1 ×1	830.0 lm
管理番号	K0181885(0)DR1	
BZ分類	BZ5	

器具効率	82%	天井	80%				70%				50%				30%				0%		
	上方光束 1%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	81%	床		10%				10%				10%				10%				0%	
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.67	0.6	4.6	3.6	2.9	2.5	4.5	3.5	2.9	2.5	4.3	3.4	2.9	2.5	4.1	3.3	2.8	2.4	2.3	
	中	0.63	0.8	5.4	4.4	3.8	3.3	5.2	4.3	3.7	3.3	5.0	4.2	3.7	3.2	4.8	4.1	3.6	3.2	3.0	
	否	0.56	1.0	5.9	5.0	4.3	3.8	5.8	4.9	4.3	3.8	5.5	4.8	4.2	3.8	5.3	4.6	4.1	3.8	3.6	
			1.25	6.4	5.5	4.9	4.4	6.2	5.5	4.9	4.4	6.0	5.3	4.8	4.4	5.7	5.1	4.7	4.3	4.1	
下方投影面積	cm <sup>2</sup>		1.5	6.7	5.9	5.3	4.9	6.6	5.8	5.3	4.8	6.3	5.7	5.2	4.8	6.0	5.5	5.1	4.7	4.5	
等価発光面積	cm <sup>2</sup>		2.0	7.2	6.5	6.0	5.5	7.0	6.4	5.9	5.5	6.7	6.2	5.8	5.4	6.5	6.0	5.7	5.3	5.1	
取付高さ	器具間隔最大限		2.5	7.4	6.9	6.4	6.0	7.3	6.8	6.3	5.9	7.0	6.6	6.2	5.8	6.8	6.4	6.1	5.8	5.5	
	横方向 (A)	縦方向 (B)	3.0	7.6	7.1	6.7	6.3	7.5	7.0	6.6	6.3	7.2	6.8	6.5	6.2	7.0	6.6	6.3	6.1	5.8	
Hm	1.25Hm	1.25Hm	4.0	7.9	7.5	7.1	6.8	7.8	7.4	7.1	6.7	7.5	7.2	6.9	6.6	7.3	7.0	6.7	6.5	6.3	
			5.0	8.1	7.7	7.4	7.1	7.9	7.6	7.3	7.1	7.7	7.4	7.2	6.9	7.4	7.2	7.0	6.8	6.5	
			7.0	8.3	8.0	7.8	7.5	8.1	7.9	7.7	7.5	7.9	7.7	7.5	7.3	7.7	7.5	7.3	7.2	6.9	
			10.0	8.4	8.2	8.0	7.9	8.3	8.1	7.9	7.8	8.1	7.9	7.8	7.6	7.8	7.7	7.6	7.5	7.2	

