

屋内照明器具特性	
品番(品名)	LGB81010
光源	LLD3000CU1 x1 795.0 lm
管理番号	K0178769(0)DR1
BZ分類	BZ10

器具効率	92%	天井	80%				70%				50%				30%				0%	
	上方光束		92%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	0%	床	10%				10%				10%				10%				0%	
室指数		照明率 (X0.01)	ZCM																	
保守率	良 0.67	0.6	40	30	24	20	34	26	21	17	23	18	15	12	13	10	8	7	0	
	中 0.63	0.8	47	38	31	27	40	32	27	23	27	22	19	16	15	13	11	10	0	
	否 0.56	1.0	52	43	37	33	44	37	32	28	30	26	23	20	17	15	13	12	0	
		1.25	57	49	43	38	48	42	37	33	33	29	26	24	19	17	15	14	0	
下方投影面積	cm ²	1.5	60	53	47	43	51	46	41	37	35	32	29	26	20	18	17	15	0	
等価発光面積	cm ²	2.0	65	59	54	50	55	50	46	43	38	35	32	30	22	20	19	18	0	
取付高さ	器具間隔最大限		2.5	67	62	58	54	58	54	50	47	40	37	35	33	23	22	20	19	0
	横方向(A)	縦方向(B)	3.0	69	65	61	58	60	56	53	50	41	39	37	35	24	23	22	21	0
Hm	0.20Hm	0.20Hm	4.0	72	68	65	62	62	59	56	54	43	41	39	38	25	24	23	22	0
			5.0	73	71	68	65	63	61	59	57	44	42	41	40	25	25	24	23	0
			7.0	75	73	71	69	65	63	61	60	45	44	43	42	26	26	25	25	0
			10.0	77	75	74	72	66	65	64	62	46	45	44	44	27	26	26	26	0

