

屋内照明器具特性	
品番 (品名)	XYM2032
光源	LED5000_85_21000 ×1 21000.0 1m
管理番号	K0160688(0)DR1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	2%	床	10%				10%				10%				10%				0%	
下方光束	98%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	5.6	4.4	3.6	3.0	5.5	4.3	3.6	3.0	5.2	4.2	3.5	3.0	5.0	4.1	3.4	3.0	2.8
	中	0.81	0.8	6.6	5.5	4.7	4.1	6.5	5.4	4.6	4.1	6.2	5.2	4.6	4.0	5.9	5.1	4.5	4.0	3.8
	否	0.77	1.0	7.3	6.2	5.4	4.9	7.1	6.1	5.4	4.8	6.8	5.9	5.3	4.8	6.5	5.8	5.2	4.7	4.5
			1.25	7.9	6.9	6.2	5.6	7.7	6.8	6.1	5.6	7.4	6.6	6.0	5.5	7.1	6.4	5.9	5.5	5.2
下方投影面積	cm ²		1.5	8.3	7.4	6.7	6.2	8.1	7.3	6.7	6.1	7.8	7.1	6.5	6.1	7.5	6.9	6.4	6.0	5.7
等価発光面積	cm ²		2.0	8.9	8.1	7.5	7.0	8.7	8.0	7.4	7.0	8.4	7.8	7.3	6.9	8.0	7.6	7.1	6.8	6.5
取付高さ	器具間隔最大限		2.5	9.2	8.6	8.1	7.6	9.1	8.5	8.0	7.5	8.7	8.2	7.8	7.4	8.4	8.0	7.6	7.3	7.0
	横方向 (A)	縦方向 (B)	3.0	9.5	8.9	8.4	8.0	9.3	8.8	8.3	8.0	9.0	8.5	8.2	7.8	8.7	8.3	8.0	7.7	7.4
Hm	1.31Hm	1.31Hm	4.0	9.8	9.3	9.0	8.6	9.6	9.2	8.9	8.5	9.3	9.0	8.6	8.4	9.0	8.7	8.5	8.2	7.9
			5.0	10.0	9.6	9.3	9.0	9.8	9.5	9.2	8.9	9.5	9.2	9.0	8.7	9.2	9.0	8.8	8.5	8.2
			7.0	10.2	9.9	9.7	9.4	10.0	9.8	9.6	9.3	9.7	9.5	9.3	9.1	9.5	9.3	9.1	9.0	8.6
			10.0	10.4	10.2	10.0	9.8	10.2	10.0	9.9	9.7	9.9	9.8	9.6	9.5	9.7	9.5	9.4	9.3	8.9

