

屋内照明器具特性

品番 (品名)	L G W C 8 5 0 8 6 Z																
光源	LDA4L - H - E17 / E / S / W / 2 × 1 440.0 1 m																
管理番号	K0172661 (0) DR 1																
B Z 分類	B Z 8																

器具効率	63 %	天井	80 %				70 %				50 %				30 %				0 %
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		床	10 %				10 %				10 %				10 %				0 %
上方光束	24 %																		
下方光束	39 %																		
室指数	照明率 (X 0.01) Z C M																		
保守率	良 0.63 中 0.6 否 0.56	0.6	2.9	2.0	1.5	1.2	2.6	1.9	1.4	1.1	2.3	1.7	1.3	1.0	1.9	1.4	1.1	0.8	0.6
		0.8	3.4	2.6	2.1	1.7	3.1	2.4	1.9	1.6	2.7	2.1	1.7	1.4	2.3	1.8	1.5	1.2	0.8
		1.0	3.8	3.0	2.4	2.0	3.5	2.8	2.3	1.9	3.0	2.4	2.0	1.7	2.5	2.1	1.7	1.5	1.1
		1.25	4.1	3.4	2.9	2.4	3.8	3.2	2.7	2.3	3.3	2.8	2.4	2.0	2.8	2.4	2.0	1.8	1.3
下方投影面積	c m ²	1.5	4.4	3.7	3.2	2.8	4.1	3.5	3.0	2.6	3.5	3.0	2.6	2.3	3.0	2.6	2.3	2.0	1.5
		2.0	4.7	4.1	3.7	3.3	4.4	3.9	3.4	3.1	3.8	3.4	3.0	2.7	3.2	2.9	2.6	2.4	1.8
取付高さ	器具間隔最大限		2.5	5.0	4.4	4.0	3.6	4.6	4.2	3.8	3.4	4.0	3.6	3.3	3.0	3.4	3.1	2.9	2.0
	横方向 (A)	縦方向 (B)	3.0	5.1	4.7	4.3	3.9	4.8	4.4	4.0	3.7	4.2	3.8	3.5	3.3	3.6	3.3	3.1	2.2
H m	1.49 H m	1.57 H m	4.0	5.4	5.0	4.6	4.3	5.0	4.7	4.4	4.1	4.4	4.1	3.8	3.6	3.8	3.6	3.4	2.5
			5.0	5.5	5.2	4.9	4.6	5.2	4.9	4.6	4.3	4.5	4.3	4.1	3.9	3.9	3.7	3.5	3.4
			7.0	5.7	5.4	5.2	4.9	5.3	5.1	4.9	4.7	4.7	4.5	4.3	4.2	4.1	3.9	3.8	2.9
			10.0	5.8	5.6	5.4	5.2	5.5	5.3	5.1	5.0	4.8	4.7	4.6	4.4	4.2	4.1	4.0	3.1

