

屋内照明器具特性	
品番 (品名)	XLY120HYB
光源	LED9999_65_400 x1 400.0 lm
管理番号	K0162679(0)D 1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	6%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	94%																																																						
保守率	良 0.59 中 0.57 否 0.54	0.6	5.5	4.2	3.4	2.9	5.3	4.1	3.4	2.8	5.0	4.0	3.3	2.8	4.7	3.8	3.2	2.8	2.5																																				
		0.8	6.4	5.2	4.4	3.8	6.2	5.1	4.4	3.8	5.9	4.9	4.3	3.7	5.6	4.8	4.2	3.7	3.4																																				
		1.0	7.1	6.0	5.2	4.6	6.9	5.8	5.1	4.5	6.5	5.6	5.0	4.4	6.2	5.4	4.8	4.4	4.1																																				
		1.25	7.7	6.6	5.9	5.3	7.5	6.5	5.8	5.2	7.1	6.3	5.6	5.1	6.7	6.0	5.5	5.0	4.7																																				
下方投影面積	c m <sup>2</sup>	1.5	8.1	7.1	6.4	5.8	7.9	7.0	6.3	5.8	7.5	6.7	6.1	5.6	7.1	6.5	5.9	5.5	5.2																																				
		2.0	8.6	7.8	7.2	6.6	8.4	7.7	7.1	6.6	8.0	7.4	6.9	6.4	7.6	7.1	6.7	6.3	5.9																																				
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.7	7.2	8.8	8.1	7.6	7.1	8.4	7.8	7.4	7.0	8.0	7.5	7.1	6.8	6.4																																			
	横方向 (A)	縦方向 (B)	3.0	9.3	8.6	8.1	7.7	9.0	8.5	8.0	7.6	8.6	8.2	7.7	7.4	8.2	7.8	7.5	7.2	6.8																																			
1.5m	1.98m	2.12m	4.0	9.6	9.1	8.6	8.3	9.4	8.9	8.5	8.1	9.0	8.6	8.2	7.9	8.6	8.3	8.0	7.7	7.3																																			
2	2.61	2.67	5.0	9.8	9.4	9.0	8.6	9.6	9.2	8.8	8.5	9.2	8.9	8.6	8.3	8.8	8.5	8.3	8.1	7.6																																			
2.5	3.25	3.25	7.0	10.0	9.7	9.4	9.1	9.8	9.5	9.3	9.0	9.4	9.2	9.0	8.7	9.1	8.9	8.7	8.5	8.1																																			
3	3.88	3.84	10.0	10.2	10.0	9.8	9.5	10.0	9.8	9.6	9.4	9.6	9.5	9.3	9.1	9.3	9.1	9.0	8.8	8.4																																			

