

# 屋内照明器具特性

品番 (品名)	L G W 5 1 7 0 6 B														
光源	LLD6300L ×1                      1270.0 1m														
管理番号	K0165623 ( 0 ) DB 1														
B Z 分類	B Z 5														

器具効率	68 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	2 %																			
下方光束	66 %																			
室指数	照明率 ( X 0.01 )																			
保守率	良 0.63	Z C M																		
	中 0.6	0.6	3.8	2.9	2.4	2.0	3.7	2.9	2.4	2.0	3.5	2.8	2.3	2.0	3.3	2.7	2.3	2.0	1.8	
	否 0.56	0.8	4.4	3.6	3.1	2.7	4.3	3.6	3.0	2.7	4.1	3.4	3.0	2.6	3.9	3.3	2.9	2.6	2.4	
下方投影面積	c m <sup>2</sup>	1.25	5.3	4.6	4.1	3.7	5.1	4.5	4.0	3.6	4.9	4.3	3.9	3.6	4.7	4.2	3.8	3.5	3.3	
等価発光面積		c m <sup>2</sup>	1.5	5.5	4.9	4.4	4.0	5.4	4.8	4.4	4.0	5.2	4.7	4.3	3.9	4.9	4.5	4.2	3.9	3.7
取付高さ	器具間隔最大限		2.5	6.2	5.7	5.3	5.0	6.0	5.6	5.2	4.9	5.8	5.4	5.1	4.8	5.5	5.2	5.0	4.7	4.5
	横方向 ( A )	縦方向 ( B )	3.0	6.3	5.9	5.6	5.3	6.2	5.8	5.5	5.2	5.9	5.6	5.3	5.1	5.7	5.4	5.2	5.0	4.8
H m	1.26 H m	1.26 H m	4.0	6.6	6.2	5.9	5.7	6.4	6.1	5.8	5.6	6.2	5.9	5.7	5.5	5.9	5.7	5.5	5.3	5.1
			5.0	6.7	6.4	6.2	5.9	6.6	6.3	6.1	5.9	6.3	6.1	5.9	5.7	6.1	5.9	5.7	5.6	5.3
			7.0	6.8	6.6	6.4	6.3	6.7	6.5	6.3	6.2	6.5	6.3	6.2	6.0	6.3	6.1	6.0	5.9	5.6
			10.0	7.0	6.8	6.7	6.5	6.9	6.7	6.6	6.4	6.6	6.5	6.4	6.3	6.4	6.3	6.2	6.1	5.8

