

屋内照明器具特性	
品番 (品名)	L G S 1 0 2 0 V
光源	L E D 3 5 0 0 _ 7 0 _ 4 4 0 × 1 4 4 0 . 0 l m
管理番号	K 0 1 6 1 6 7 7 (0) D R 1
B Z 分類	B Z 1 / 1 . 1 / B Z 2 / 8 . 5 / B Z 1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		1 0 0 %																					
保守率		良 中 否	0 . 6	7 3	6 4	5 9	5 5	7 2	6 4	5 8	5 5	7 0	6 3	5 8	5 5	6 8	6 2	5 8	5 5	5 3			
			0 . 8	8 0	7 2	6 7	6 3	7 9	7 2	6 7	6 3	7 7	7 1	6 6	6 3	7 5	7 0	6 6	6 3	6 1			
			1 . 0	8 5	7 8	7 3	6 9	8 4	7 8	7 3	6 9	8 2	7 6	7 2	6 9	8 0	7 5	7 1	6 8	6 7			
			0 . 5 6	1 . 2 5	9 0	8 3	7 9	7 5	8 8	8 3	7 8	7 5	8 6	8 1	7 7	7 4	8 4	8 0	7 6	7 4	7 2		
下方投影面積		c m ²	1 . 5	9 3	8 7	8 3	7 9	9 1	8 6	8 2	7 9	8 9	8 5	8 1	7 8	8 7	8 3	8 0	7 8	7 6			
			2 . 0	9 6	9 2	8 8	8 5	9 5	9 1	8 8	8 5	9 3	8 9	8 6	8 4	9 1	8 8	8 5	8 3	8 1			
取付 高さ	器具間隔最大限		2 . 5	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	9 0	8 7	9 3	9 1	8 8	8 6	8 4			
	横方向 (A)	縦方向 (B)	3 . 0	1 0 0	9 7	9 4	9 2	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 2	9 1	8 9	8 7			
H m	0 . 4 7 H m	0 . 4 7 H m	4 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	9 0			
			5 . 0	1 0 3	1 0 1	9 9	9 8	1 0 2	1 0 0	9 9	9 7	1 0 0	9 8	9 7	9 5	9 8	9 6	9 5	9 4	9 2			
			7 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4			
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 9	9 8	9 5			

