

屋内照明器具特性	
品番 (品名)	L G D 9 4 0 4
光源	L L D 2 0 0 0 C U 1 × 1 5 6 6 . 0 l m
管理番号	K 0 1 7 8 9 4 9 (0) D R 1
B Z 分類	B Z 4

器具効率		8 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 2	4 2	3 5	3 1	5 1	4 1	3 5	3 1	4 9	4 1	3 5	3 0	4 7	4 0	3 4	3 0	2 9
			0 . 6 3	0 . 8	6 2	5 2	4 5	4 0	6 0	5 1	4 5	4 0	5 8	5 0	4 4	4 0	5 6	4 9	4 4	4 0	3 8
			1 . 0	1 . 0	6 8	5 9	5 2	4 8	6 6	5 8	5 2	4 7	6 4	5 7	5 1	4 7	6 2	5 5	5 1	4 7	4 5
			0 . 5 6	1 . 2 5	7 3	6 5	5 9	5 4	7 2	6 4	5 9	5 4	6 9	6 3	5 8	5 4	6 7	6 1	5 7	5 3	5 1
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	1 . 5	7 7	6 9	6 4	5 9	7 5	6 9	6 3	5 9	7 3	6 7	6 2	5 9	7 0	6 5	6 1	5 8	5 6
			2 . 0	2 . 0	8 1	7 6	7 1	6 7	8 0	7 5	7 0	6 6	7 8	7 3	6 9	6 6	7 5	7 1	6 8	6 5	6 3
			2 . 5	2 . 5	8 4	7 9	7 5	7 2	8 3	7 9	7 5	7 1	8 1	7 7	7 3	7 0	7 8	7 5	7 2	7 0	6 7
取付 高さ	器具間隔最大限		3 . 0	8 6	8 2	7 8	7 5	8 5	8 1	7 8	7 5	8 3	7 9	7 6	7 4	8 0	7 8	7 5	7 3	7 1	
	横方向 (A) 縦方向 (B)																				
H m	1 . 2 6 H m	1 . 2 6 H m	4 . 0	8 9	8 6	8 3	8 0	8 8	8 5	8 2	7 9	8 5	8 3	8 0	7 8	8 3	8 1	7 9	7 7	7 5	
			5 . 0	9 1	8 8	8 5	8 3	8 9	8 7	8 4	8 2	8 7	8 5	8 3	8 1	8 5	8 3	8 1	8 0	7 7	
			7 . 0	9 2	9 0	8 8	8 7	9 1	8 9	8 7	8 6	8 9	8 7	8 6	8 4	8 7	8 5	8 4	8 3	8 0	
			1 0 . 0	9 4	9 2	9 1	8 9	9 2	9 1	9 0	8 9	9 0	8 9	8 8	8 7	8 8	8 7	8 6	8 5	8 3	

