

# 屋内照明器具特性

品番 (品名)	XLX439DEV														
光源	LED3500_85_3040 x1 3040.0 lm														
管理番号	K0130919 (* ) DB 1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	4 %	室指数	照明率 ( X0.01 )																ZCM		
下方光束	96 %																				
保守率	良 中 否	0.83	0.6	55	42	34	29	53	42	34	29	51	40	33	28	48	39	33	28	26	
		0.81	0.8	65	53	45	39	63	52	44	38	60	50	43	38	57	48	42	37	35	
		0.77	1.0	71	60	52	46	69	59	51	46	66	57	50	45	62	55	49	44	42	
			1.25	77	67	59	53	75	66	58	53	71	63	57	52	68	61	56	51	48	
下方投影面積 等価発光面積	c m <sup>2</sup>	1.5	81	72	65	59	79	70	64	58	75	68	62	57	72	66	60	56	53		
		2.0	87	79	72	67	85	77	71	66	81	75	69	65	77	72	68	64	60		
		2.5	90	84	78	73	88	82	77	72	85	79	74	70	81	76	72	69	66		
取付 高さ	器具間隔最大限		3.0	93	87	82	77	91	85	80	76	87	82	78	75	84	80	76	73	69	
	横方向 (A)	縦方向 (B)																			
1.5m	1.99 m	2.17 m	4.0	96	91	87	83	94	90	86	82	91	87	83	80	87	84	81	78	75	
2	2.62	2.74	5.0	98	94	90	87	96	93	89	86	93	89	86	84	89	87	84	82	78	
2.5	3.26	3.32	7.0	101	97	95	92	99	96	93	91	95	93	90	88	92	90	88	86	82	
3	3.89	3.92	10.0	102	100	98	96	101	99	96	95	97	95	94	92	94	92	91	90	86	

