

屋内照明器具特性	
品番 (品名)	LGB57582Z
光源	LDA13L-G/Z100E/S/W ×5 1520.0 l m
管理番号	K0164510 (0) DB 1
BZ分類	BZ6

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	44	33	26	21	42	31	25	20	37	29	23	19	33	26	21	17	14
			0.63	0.8	52	41	33	28	49	39	32	27	44	36	30	25	39	32	27	23	20
			0.56	1.0	57	47	39	34	54	44	38	32	48	40	35	30	43	37	32	28	23
				1.25	62	52	45	39	59	50	43	38	52	45	40	35	47	41	36	33	27
下方投影面積		cm ²		1.5	65	56	49	44	62	54	48	42	56	49	44	39	50	44	40	36	31
			等価発光面積	cm ²	2.0	70	63	56	51	67	60	54	49	60	54	50	46	54	49	45	42
取付 高さ	器具間隔最大限			2.5	74	67	61	56	70	64	59	54	63	58	54	50	57	53	49	46	39
	横方向 (A) 縦方向 (B)			3.0	76	70	65	60	72	67	62	58	65	61	57	53	59	55	52	49	42
H m	1.19 H m 1.18 H m			4.0	79	74	70	65	75	71	67	63	68	65	61	58	62	59	56	54	46
				5.0	81	77	73	69	77	73	70	67	70	67	64	62	64	61	59	57	49
				7.0	83	80	77	74	80	77	74	71	73	70	68	66	66	64	62	61	52
				10.0	85	83	80	78	82	79	77	75	75	73	71	69	68	67	65	64	55

