

屋内照明器具特性

品番 (品名)	LGB57490K	
光源	LDA7L-D-G/S/Z6 x4	810.0 lm
管理番号	K0166333(0)DB1	
BZ分類	BZ6	

器具効率	89%	天井	80%				70%				50%				30%				0%		
	上方光束		31%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	58%	床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	4.5	3.4	2.7	2.3	4.2	3.2	2.6	2.2	3.7	2.9	2.4	2.0	3.2	2.6	2.2	1.8	1.5	
	中	0.63	0.8	5.2	4.2	3.5	3.0	4.9	4.0	3.3	2.9	4.3	3.6	3.0	2.6	3.8	3.2	2.7	2.4	1.9	
	否	0.56	1.0	5.8	4.8	4.1	3.5	5.4	4.5	3.9	3.4	4.7	4.0	3.5	3.1	4.1	3.6	3.2	2.8	2.3	
			1.25	6.2	5.3	4.6	4.1	5.8	5.0	4.4	3.9	5.1	4.5	4.0	3.6	4.5	4.0	3.6	3.2	2.6	
下方投影面積	cm ²		1.5	6.6	5.7	5.1	4.5	6.2	5.4	4.8	4.3	5.4	4.8	4.4	4.0	4.8	4.3	3.9	3.6	2.9	
等価発光面積	cm ²		2.0	7.0	6.3	5.7	5.2	6.6	6.0	5.4	5.0	5.8	5.3	4.9	4.5	5.1	4.7	4.4	4.1	3.3	
取付高さ	器具間隔最大限		2.5	7.3	6.7	6.2	5.7	6.9	6.3	5.9	5.4	6.1	5.7	5.3	4.9	5.4	5.0	4.7	4.4	3.6	
	横方向 (A)	縦方向 (B)	3.0	7.6	7.0	6.5	6.1	7.1	6.6	6.2	5.8	6.3	5.9	5.6	5.2	5.6	5.2	5.0	4.7	3.8	
Hm	1.37Hm	1.36Hm	4.0	7.8	7.4	7.0	6.6	7.4	7.0	6.6	6.3	6.6	6.3	5.9	5.7	5.8	5.5	5.3	5.1	4.2	
			5.0	8.0	7.6	7.3	6.9	7.6	7.2	6.9	6.6	6.8	6.5	6.2	6.0	6.0	5.8	5.5	5.3	4.4	
			7.0	8.2	7.9	7.6	7.4	7.8	7.5	7.3	7.0	7.0	6.7	6.5	6.3	6.2	6.0	5.8	5.7	4.7	
			10.0	8.4	8.2	8.0	7.7	8.0	7.8	7.6	7.4	7.2	7.0	6.8	6.7	6.4	6.2	6.1	6.0	4.9	

