

屋内照明器具特性	
品番 (品名)	L G S 9 0 0 0
光源	L L D 3 0 0 0 C U 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 9 0 9 9 (0) D R 1
B Z 分類	B Z 5

器具効率		9 6 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 4	4 2	3 5	2 9	5 3	4 2	3 4	2 9	5 0	4 0	3 4	2 9	4 8	3 9	3 3	2 9	2 7
			0 . 6 3	0 . 8	6 3	5 2	4 5	3 9	6 2	5 2	4 4	3 9	5 9	5 0	4 4	3 9	5 7	4 9	4 3	3 9	3 6
			0 . 5 6	1 . 0	7 0	5 9	5 2	4 6	6 8	5 9	5 2	4 6	6 5	5 7	5 1	4 6	6 3	5 5	5 0	4 5	4 3
				1 . 2 5	7 5	6 6	5 9	5 4	7 4	6 5	5 8	5 3	7 1	6 3	5 7	5 3	6 8	6 2	5 6	5 2	5 0
下方投影面積 等価発光面積		c m ² c m ²		1 . 5	7 9	7 1	6 4	5 9	7 8	7 0	6 4	5 9	7 5	6 8	6 2	5 8	7 2	6 6	6 1	5 7	5 5
				2 . 0	8 5	7 8	7 2	6 7	8 3	7 7	7 1	6 6	8 0	7 4	7 0	6 6	7 7	7 2	6 8	6 5	6 2
				2 . 5	8 8	8 2	7 7	7 2	8 7	8 1	7 6	7 2	8 4	7 9	7 4	7 1	8 1	7 7	7 3	7 0	6 7
取付 高さ	器具間隔最大限			3 . 0	9 1	8 5	8 1	7 6	8 9	8 4	8 0	7 6	8 6	8 2	7 8	7 5	8 3	8 0	7 6	7 4	7 1
	横方向 (A)	縦方向 (B)		4 . 0	9 4	8 9	8 5	8 2	9 2	8 8	8 5	8 1	8 9	8 6	8 3	8 0	8 6	8 4	8 1	7 9	7 6
H m	1 . 2 9 H m	1 . 2 9 H m		5 . 0	9 5	9 2	8 9	8 6	9 4	9 1	8 8	8 5	9 1	8 8	8 6	8 3	8 8	8 6	8 4	8 2	7 9
				7 . 0	9 8	9 5	9 2	9 0	9 6	9 4	9 1	8 9	9 3	9 1	8 9	8 8	9 1	8 9	8 7	8 6	8 3
				1 0 . 0	9 9	9 7	9 5	9 4	9 8	9 6	9 4	9 3	9 5	9 4	9 2	9 1	9 3	9 1	9 0	8 9	8 6

