

屋内照明器具特性	
品番 (品名)	L G S 3 5 0 3
光源	LED2700_70_650 ×1 650.0 l m
管理番号	K0164326 (0) D 1
B Z 分類	BZ4 / 0.9 / BZ3

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
			室指数	照明率 (X 0 . 0 1) Z C M																					
保守率		良 中 否	0 . 6 7	0 . 6	6 0	4 9	4 2	3 7	5 9	4 8	4 1	3 6	5 7	4 7	4 1	3 6	5 5	4 6	4 1	3 6	3 4				
			0 . 6 3	0 . 8	7 1	6 0	5 3	4 8	7 0	6 0	5 3	4 8	6 7	5 8	5 2	4 8	6 5	5 7	5 2	4 8	4 6				
			0 . 5 6	1 . 0	7 8	6 8	6 1	5 6	7 6	6 7	6 1	5 6	7 4	6 6	6 0	5 6	7 1	6 5	5 9	5 5	5 3				
				1 . 2 5	8 4	7 5	6 9	6 4	8 2	7 4	6 8	6 4	7 9	7 3	6 7	6 3	7 7	7 1	6 7	6 3	6 1				
下方投影面積 等価発光面積		c m ² c m ²		1 . 5	8 7	8 0	7 4	6 9	8 6	7 9	7 4	6 9	8 3	7 7	7 2	6 8	8 1	7 6	7 1	6 8	6 6				
				2 . 0	9 3	8 6	8 1	7 7	9 1	8 5	8 1	7 7	8 8	8 4	7 9	7 6	8 6	8 2	7 8	7 5	7 3				
取付 高さ	器具間隔最大限			2 . 5	9 6	9 1	8 6	8 2	9 4	8 9	8 5	8 2	9 2	8 7	8 4	8 1	8 9	8 6	8 3	8 0	7 8				
	横方向 (A)	縦方向 (B)		3 . 0	9 8	9 3	8 9	8 6	9 6	9 2	8 9	8 5	9 4	9 0	8 7	8 4	9 1	8 8	8 6	8 3	8 1				
H m	1 . 2 6 H m	1 . 2 6 H m		4 . 0	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 2	9 0	8 8	8 5				
				5 . 0	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 6	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 0	8 8				
				7 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 7	1 0 0	9 8	9 7	9 5	9 8	9 6	9 5	9 4	9 1				
				1 0 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4				

