

# 屋内照明器具特性

品番 (品名)	LGB58101	
光源	LLD5000LCC1 ×1	1140.0 lm
管理番号	K0190393(0)DR1	
BZ分類	BZ3	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 3%		下方光束 97%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.67	0.6	64	53	46	42	62	53	46	42	60	51	46	41	58	50	45	41	39
	中	0.63	0.8	74	64	58	53	72	63	57	53	70	62	56	52	67	60	56	52	50
	否	0.56	1.0	80	71	65	61	78	70	65	60	76	69	64	60	73	67	63	59	57
			1.25	85	78	72	67	84	77	71	67	81	75	70	66	78	73	69	66	63
下方投影面積	cm <sup>2</sup>		1.5	89	82	77	72	87	81	76	72	84	79	75	71	81	77	73	70	68
等価発光面積	cm <sup>2</sup>		2.0	93	88	83	79	92	87	82	79	89	84	81	78	86	82	79	76	74
取付高さ	器具間隔最大限		2.5	96	91	87	84	95	90	86	83	91	88	85	82	89	86	83	80	78
	横方向 (A)	縦方向 (B)	3.0	98	94	90	87	96	93	89	86	93	90	87	85	90	88	85	83	80
Hm	1.26Hm	1.26Hm	4.0	100	97	94	92	99	96	93	91	96	93	91	89	93	91	89	87	84
			5.0	102	99	97	94	100	98	96	93	97	95	93	91	94	93	91	90	86
			7.0	103	101	100	98	102	100	98	97	99	97	96	95	96	95	94	92	89
			10.0	105	103	102	101	103	102	101	99	100	99	98	97	97	96	96	95	91

