

屋内照明器具特性

品番 (品名)	LGB80525F	
光源	LDA4L-H-E17/S/4 x1	440.0lm
管理番号	K0169407(1)DR1	
BZ分類	BZ10/0.7/BZ9/0.9/BZ8/1.8/BZ7	

器具効率	22%	天井	80%				70%				50%				30%				0%	
	上方光束		7%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	15%	床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	9	6	4	3	8	6	4	3	7	5	4	2	6	4	3	2	1
	中	0.63	0.8	11	8	6	5	10	8	6	5	9	7	5	4	8	6	5	4	2
	否	0.56	1.0	13	10	8	6	12	9	7	6	10	8	7	5	9	7	6	5	3
下方投影面積		cm ²	1.25	14	11	9	8	13	11	9	8	11	9	8	7	10	8	7	6	4
	等価発光面積	cm ²	1.5	15	13	11	9	14	12	10	9	12	10	9	8	10	9	8	7	5
取付高さ	器具間隔最大限		2.5	17	15	14	13	16	15	13	12	14	13	12	11	12	11	10	10	8
	横方向 (A)	縦方向 (B)	3.0	18	16	15	14	17	15	14	13	15	14	13	12	13	12	11	10	8
Hm	0.00Hm	0.20Hm	4.0	19	17	16	15	18	16	15	14	16	15	14	13	14	13	12	12	9
			5.0	19	18	17	16	18	17	16	15	16	15	14	14	14	14	13	12	10
			7.0	20	19	18	17	19	18	17	16	17	16	15	15	15	14	14	13	11
			10.0	20	20	19	18	19	19	18	17	17	17	16	16	15	15	15	14	12

