

屋内照明器具特性	
品番 (品名)	L G S 9 5 0 0
光源	L L D 4 0 0 0 L C S 1 × 1 8 3 0 . 0 l m
管理番号	K 0 1 8 3 2 7 2 (0) D R 1
B Z 分類	B Z 5

器具効率		8 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 % 8 3 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	4 7	3 7	3 0	2 6	4 6	3 6	3 0	2 5	4 4	3 5	2 9	2 5	4 2	3 4	2 9	2 5	2 3	
			0 . 6 3	0 . 8	5 5	4 5	3 9	3 4	5 4	4 5	3 8	3 4	5 2	4 3	3 8	3 3	4 9	4 2	3 7	3 3	3 1	
			0 . 5 6	1 . 0	6 1	5 1	4 5	4 0	5 9	5 1	4 4	3 9	5 7	4 9	4 3	3 9	5 4	4 8	4 3	3 9	3 7	
				1 . 2 5	6 6	5 7	5 1	4 6	6 4	5 6	5 0	4 5	6 1	5 4	4 9	4 5	5 9	5 3	4 8	4 4	4 2	
下方投影面積		c m ²	1 . 5	6 9	6 1	5 5	5 0	6 8	6 0	5 4	5 0	6 5	5 8	5 3	4 9	6 2	5 7	5 2	4 9	4 6		
等価発光面積		c m ²	2 . 0	7 4	6 7	6 1	5 7	7 2	6 6	6 1	5 6	6 9	6 4	6 0	5 6	6 7	6 2	5 8	5 5	5 3		
取付 高さ	器具間隔最大限		2 . 5	7 7	7 1	6 6	6 2	7 5	7 0	6 5	6 1	7 2	6 8	6 4	6 0	7 0	6 6	6 2	5 9	5 7		
	横方向 (A) 縦方向 (B)		3 . 0	7 9	7 4	6 9	6 5	7 7	7 2	6 8	6 5	7 4	7 0	6 7	6 4	7 2	6 8	6 5	6 3	6 0		
H m	1 . 2 5 H m	1 . 2 5 H m	4 . 0	8 1	7 7	7 3	7 0	8 0	7 6	7 3	6 9	7 7	7 4	7 1	6 8	7 5	7 2	6 9	6 7	6 5		
			5 . 0	8 3	8 0	7 6	7 3	8 2	7 8	7 5	7 3	7 9	7 6	7 4	7 1	7 7	7 4	7 2	7 0	6 7		
			7 . 0	8 5	8 2	8 0	7 8	8 4	8 1	7 9	7 7	8 1	7 9	7 7	7 5	7 9	7 7	7 5	7 4	7 1		
			1 0 . 0	8 7	8 5	8 3	8 1	8 5	8 4	8 2	8 0	8 3	8 1	8 0	7 8	8 1	7 9	7 8	7 7	7 4		

