

屋内照明器具特性	
品番 (品名)	L G S 9 5 0 1
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184322 (0) DR 1
B Z 分類	B Z 4

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	42	34	28	25	41	33	28	25	39	33	28	25	38	32	28	24	23
			0.63	0.8	49	41	36	32	48	41	36	32	46	40	36	32	45	39	35	32	31
			0.56	1.0	54	47	42	38	53	46	41	38	51	45	41	38	49	44	40	37	36
				1.25	58	52	47	43	57	51	47	43	55	50	46	43	53	49	45	42	41
下方投影面積		c m ²		1.5	61	55	51	47	60	55	50	47	58	53	50	47	56	52	49	46	45
			等価発光面積	c m ²	2.0	65	60	56	53	64	59	56	53	62	58	55	52	60	57	54	52
取付 高さ	器具間隔最大限			2.5	67	63	60	57	66	62	59	56	64	61	58	56	62	59	57	55	53
	横方向 (A) 縦方向 (B)			3.0	69	65	62	60	68	64	62	59	66	63	61	58	64	62	60	58	56
H m	1.23 H m 1.23 H m			4.0	71	68	66	63	70	67	65	63	68	66	64	62	66	64	63	61	59
				5.0	72	70	68	66	71	69	67	65	69	67	66	64	67	66	65	63	61
				7.0	73	72	70	69	72	71	69	68	71	69	68	67	69	68	67	66	64
				10.0	74	73	72	71	73	72	71	70	72	71	70	69	70	69	69	68	66

