

屋内照明器具特性	
品番 (品名)	LGS9501
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 l m
管理番号	K0184327 (0) DR 1
BZ分類	BZ1

器具効率		90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		90 %																							
保守率		良	0.67	0.6	70	63	58	55	69	62	58	55	67	62	58	55	66	61	58	55	54				
		中	0.63	0.8	76	70	66	63	76	70	66	63	74	69	65	63	72	68	65	63	61				
		否	0.56	1.0	81	75	71	68	80	75	71	68	78	74	70	68	76	73	70	67	66				
				1.25	84	79	76	73	83	79	75	72	81	77	74	72	80	76	74	72	70				
下方投影面積		c m ²		1.5	86	82	79	76	85	81	78	76	83	80	77	75	82	79	77	75	73				
等価発光面積		c m ²		2.0	89	86	83	80	88	85	82	80	86	84	81	79	84	82	80	79	77				
取付	器具間隔最大限			2.5	91	88	85	83	90	87	85	83	88	86	84	82	86	84	83	81	79				
高さ	横方向 (A)		縦方向 (B)	3.0	92	90	87	85	91	89	87	85	89	87	85	84	87	86	84	83	81				
H m	0.74 H m		0.74 H m	4.0	94	92	90	88	92	91	89	88	90	89	88	86	89	87	86	85	83				
				5.0	94	93	91	90	93	92	90	89	91	90	89	88	89	88	87	87	84				
				7.0	95	94	93	92	94	93	92	91	92	91	91	90	90	90	89	88	86				
				10.0	96	95	94	94	95	94	94	93	93	92	92	91	91	91	90	90	87				

