

屋内照明器具特性

品番 (品名)	FYY22730				
光源	LED3000_85_910 x1		910.0 lm		
管理番号	K0166072(0)DB1				
BZ分類	BZ6/1.4/BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		100%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.83	0.6	52	39	30	24	51	38	30	24	48	37	29	24	46	36	29	24	22	
	中	0.81	0.8	62	49	41	34	61	49	40	34	58	47	40	34	55	46	39	34	32	
	否	0.77	1.0	69	57	49	42	68	56	48	42	64	55	47	42	61	53	47	41	39	
			1.25	76	65	57	50	74	64	56	50	71	62	55	50	68	60	54	49	47	
下方投影面積	c m ²		1.5	81	71	63	57	79	70	62	57	75	68	61	56	72	66	60	55	53	
	等価発光面積		c m ²	2.0	87	79	72	66	85	78	71	66	82	75	70	65	79	73	69	64	62
取付高さ	器具間隔最大限		2.5	91	84	78	73	89	83	77	72	86	80	76	71	83	78	74	71	68	
	横方向 (A)	縦方向 (B)	3.0	94	88	82	78	92	86	81	77	89	84	80	76	86	82	78	75	72	
1.5m	0	2.01m	4.0	97	92	88	84	96	91	87	84	93	89	85	82	90	87	84	81	78	
2	0	2.66	5.0	99	95	92	88	98	94	91	88	95	92	89	86	92	90	87	85	82	
2.5	0	3.3	7.0	102	99	96	94	101	98	95	93	98	95	93	91	95	93	91	90	87	
3	0	3.96	10.0	104	102	100	98	102	100	99	97	100	98	97	95	97	96	95	93	90	

