

屋内照明器具特性

品番 (品名)	XL X 2 0 0 M E D J														
光源	LED 6 5 0 0 _ 8 5 _ 7 3 0 × 1 7 3 0 . 0 1 m														
管理番号	K 0 1 2 9 8 0 7 (7) D B 1														
B Z 分類	B Z 5 / 0 . 7 / B Z 4														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X 0 . 0 1)															Z C M		
保守率	良 中 否	0.81	0.6	5.8	4.6	3.9	3.3	5.7	4.6	3.8	3.3	5.4	4.4	3.8	3.3	5.2	4.3	3.7	3.3	3.1
		0.77	0.8	6.8	5.7	5.0	4.4	6.7	5.7	4.9	4.4	6.4	5.5	4.9	4.4	6.2	5.4	4.8	4.4	4.2
			1.0	7.5	6.5	5.8	5.2	7.4	6.4	5.7	5.2	7.1	6.3	5.6	5.2	6.8	6.1	5.6	5.1	4.9
		0.68	1.25	8.1	7.2	6.5	6.0	8.0	7.1	6.5	6.0	7.7	6.9	6.4	5.9	7.4	6.8	6.3	5.9	5.6
下方投影面積	c m ²	1.5	8.5	7.7	7.1	6.5	8.4	7.6	7.0	6.5	8.1	7.4	6.9	6.4	7.8	7.2	6.8	6.4	6.2	
		2.0	9.1	8.4	7.8	7.4	8.9	8.3	7.8	7.3	8.6	8.1	7.6	7.2	8.3	7.9	7.5	7.2	6.9	
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.3	7.9	9.2	8.7	8.3	7.9	9.0	8.5	8.1	7.8	8.7	8.3	8.0	7.7	7.4
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.7	8.3	9.5	9.0	8.6	8.3	9.2	8.8	8.5	8.1	8.9	8.6	8.3	8.0	7.8
1.5 m	1.97 m	2.01 m	4.0	9.9	9.5	9.2	8.9	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.7	9.2	9.0	8.7	8.5	8.3
2	2.62	2.64	5.0	10.1	9.8	9.5	9.2	10.0	9.7	9.4	9.1	9.7	9.4	9.2	9.0	9.4	9.2	9.0	8.8	8.6
2.5	3.26	3.27	7.0	10.3	10.1	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.4	9.7	9.5	9.4	9.2	8.9
3	3.91	3.9	10.0	10.5	10.3	10.1	10.0	10.3	10.2	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

