

屋内照明器具特性	
品番 (品名)	LRD9 1 0 0
光源	LLD3020LCB1 ×1 795.0 l m
管理番号	K0175980 (0) DR 1
B Z 分類	BZ1

器具効率		63 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	52	48	45	43	51	47	45	43	50	47	45	43	50	47	45	43	42
			0.6	0.8	56	52	50	48	55	52	49	48	54	51	49	48	53	51	49	47	47
			0.56	1.0	58	55	53	51	57	54	52	51	56	54	52	50	55	53	52	50	49
				1.25	60	57	55	53	59	57	55	53	58	56	54	53	57	55	54	53	52
下方投影面積		c m ²		1.5	61	59	57	55	61	58	57	55	60	58	56	55	58	57	55	54	53
				2.0	63	61	59	58	62	61	59	58	61	60	58	57	60	59	58	57	56
取付 高さ	器具間隔最大限			2.5	64	62	61	60	63	62	60	59	62	61	60	59	61	60	59	58	57
	横方向 (A)	縦方向 (B)		3.0	65	63	62	61	64	63	62	60	63	62	61	60	61	61	60	59	58
H m	0.41 H m	0.41 H m		4.0	66	64	63	62	65	64	63	62	63	63	62	61	62	62	61	60	59
				5.0	66	65	64	63	65	64	64	63	64	63	63	62	63	62	62	61	60
				7.0	67	66	65	65	66	65	65	64	64	64	63	63	63	63	62	62	60
				10.0	67	66	66	66	66	66	65	65	65	65	64	64	64	63	63	63	61

