

# 屋内照明器具特性

品番 (品名)	FYY22240				
光源	LED4000_85_2360 x1 2360.0 1m				
管理番号	K0166073(0)DB1				
BZ分類	BZ5/3.5/BZ6/4.5/BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.83	0.6	55	42	34	28	53	41	34	28	51	40	33	28	49	39	33	28	26
	中	0.81	0.8	64	52	44	38	63	51	43	37	60	50	43	37	57	48	42	37	35
	否	0.77	1.0	71	59	51	44	69	58	50	44	66	56	49	44	63	55	49	44	41
			1.25	76	66	58	51	75	65	57	51	71	63	56	51	68	61	55	50	48
下方投影面積		cm <sup>2</sup>	1.5	81	71	63	57	79	70	62	56	75	67	61	56	72	66	60	55	53
等価発光面積		cm <sup>2</sup>	2.0	86	78	71	65	84	77	70	65	81	74	69	64	78	72	67	63	60
取付高さ	器具間隔最大限		2.5	90	83	76	71	88	81	75	70	85	79	74	69	82	77	72	69	66
	横方向 (A)	縦方向 (B)	3.0	93	86	80	75	91	85	79	75	88	82	78	74	85	80	76	73	70
1.5m	1.93m	1.8m	4.0	96	91	86	82	94	89	85	81	91	87	83	80	88	85	82	79	76
2	2.49	2.42	5.0	98	94	90	86	97	93	89	85	94	90	87	84	91	88	85	82	80
2.5	3.05	3.01	7.0	101	97	94	91	99	96	93	91	96	94	91	89	94	92	89	87	84
3	3.62	3.68	10.0	103	101	98	96	102	99	97	95	99	97	95	93	96	95	93	91	88

