

屋内照明器具特性	
品番 (品名)	L R D 9 1 0 0
光源	L L D 2 0 0 0 L C T 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 0 4 7 4 (0) D R 1
B Z 分類	B Z 3

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01)															
保守率		良 中 否	0.63	0.6	3.9	3.2	2.8	2.5	3.8	3.2	2.8	2.5	3.7	3.1	2.8	2.5	3.6	3.1	2.7	2.5	2.4	
			0.6	0.8	4.6	3.9	3.5	3.2	4.5	3.9	3.5	3.2	4.3	3.8	3.5	3.2	4.2	3.8	3.4	3.2	3.1	
			0.56	1.0	5.0	4.4	4.0	3.7	4.9	4.4	4.0	3.7	4.7	4.3	3.9	3.7	4.6	4.2	3.9	3.7	3.5	
				1.25	5.3	4.8	4.5	4.2	5.3	4.8	4.4	4.2	5.1	4.7	4.4	4.1	4.9	4.6	4.3	4.1	4.0	
下方投影面積		cm ²		1.5	5.6	5.1	4.8	4.5	5.5	5.1	4.7	4.5	5.3	5.0	4.7	4.4	5.2	4.9	4.6	4.4	4.3	
				2.0	5.9	5.5	5.2	5.0	5.8	5.5	5.2	4.9	5.6	5.3	5.1	4.9	5.5	5.2	5.0	4.8	4.7	
取付 高さ	器具間隔最大限			2.5	6.1	5.8	5.5	5.3	6.0	5.7	5.5	5.2	5.8	5.6	5.4	5.2	5.7	5.5	5.3	5.1	5.0	
	横方向 (A) 縦方向 (B)			3.0	6.2	5.9	5.7	5.5	6.1	5.9	5.6	5.5	5.9	5.7	5.6	5.4	5.8	5.6	5.5	5.3	5.2	
Hm	1.21Hm	1.21Hm		4.0	6.4	6.1	6.0	5.8	6.3	6.1	5.9	5.7	6.1	5.9	5.8	5.7	6.0	5.8	5.7	5.6	5.4	
				5.0	6.4	6.3	6.1	6.0	6.4	6.2	6.1	5.9	6.2	6.1	5.9	5.8	6.1	5.9	5.8	5.7	5.6	
				7.0	6.6	6.4	6.3	6.2	6.5	6.4	6.2	6.1	6.3	6.2	6.1	6.0	6.2	6.1	6.0	5.9	5.8	
				10.0	6.6	6.5	6.5	6.4	6.6	6.5	6.4	6.3	6.4	6.3	6.3	6.2	6.3	6.2	6.1	6.1	5.9	

