

屋内照明器具特性	
品番 (品名)	LRD9 1 0 2
光源	LLD3020LCB1 ×1 795.0 l m
管理番号	K0175977 (0) DR 1
B Z 分類	BZ1

器具効率		53 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		53 %																							
保守率		良	0.63	0.6	44	40	38	37	43	40	38	37	43	40	38	37	42	40	38	37	36				
		中	0.6	0.8	47	44	42	41	47	44	42	41	46	43	42	40	45	43	41	40	40				
		否	1.0	1.0	49	47	45	43	49	46	44	43	48	46	44	43	47	45	44	43	42				
		0.56	1.25	51	49	47	45	50	48	47	45	49	48	46	45	49	47	46	45	44					
下方投影面積		c m ²		1.5	52	50	48	47	52	50	48	47	51	49	48	46	50	48	47	46	45				
等価発光面積		c m ²		2.0	54	52	50	49	53	51	50	49	52	51	49	49	51	50	49	48	47				
取付 高さ	器具間隔最大限			2.5	54	53	52	51	54	52	51	50	53	52	51	50	52	51	50	49	48				
	横方向 (A)		縦方向 (B)	3.0	55	54	53	52	54	53	52	51	53	52	51	51	52	51	51	50	49				
H m	0.41 H m	0.41 H m	4.0	56	55	54	53	55	54	53	53	54	53	53	52	53	52	52	51	50					
			5.0	56	55	55	54	55	55	54	53	54	54	53	53	53	53	53	52	51					
			7.0	57	56	55	55	56	55	55	54	55	54	54	54	54	54	53	53	51					
			10.0	57	56	56	56	56	56	56	55	55	55	54	54	54	54	53	53	52					

