

屋内照明器具特性	
品番 (品名)	L R D 9 1 0 2
光源	L L D 2 0 0 0 L C T 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 0 4 7 5 (0) D R 1
B Z 分類	B Z 3

器具効率		5 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																		下方光束		5 4 %
保守率		良 0 . 6 3 中 0 . 6 否 0 . 5 6		0 . 6 0 . 8 1 . 0	3 3 3 9 4 2	2 7 3 4 3 8	2 4 3 0 3 4	2 1 2 7 3 2	3 3 3 8 4 2	2 7 3 3 3 7	2 4 3 0 3 4	2 1 2 7 3 1	3 2 3 7 4 0	2 7 3 3 3 6	2 3 2 9 3 3	2 1 2 7 3 1	3 0 3 6 3 9	2 6 3 2 3 6	2 3 2 9 3 3	2 1 2 7 3 1	2 0 2 6 3 0			
下方投影面積		c m ²	1 . 2 5	4 5	4 1	3 8	3 5	4 5	4 1	3 8	3 5	4 3	4 0	3 7	3 5	4 2	3 9	3 7	3 5	3 4				
等価発光面積		c m ²	1 . 5	4 7	4 4	4 1	3 8	4 7	4 3	4 0	3 8	4 5	4 2	4 0	3 8	4 4	4 1	3 9	3 7	3 6				
2 . 0			5 0	4 7	4 4	4 2	4 9	4 6	4 4	4 2	4 8	4 5	4 3	4 2	4 6	4 4	4 3	4 1	4 0					
取付高さ	器具間隔最大限		2 . 5	5 2	4 9	4 7	4 5	5 1	4 8	4 6	4 5	4 9	4 7	4 6	4 4	4 8	4 6	4 5	4 4	4 2				
	横方向 (A) 縦方向 (B)		3 . 0	5 3	5 0	4 8	4 7	5 2	5 0	4 8	4 6	5 0	4 9	4 7	4 6	4 9	4 8	4 6	4 5	4 4				
H m	1 . 2 1 H m	1 . 2 1 H m	4 . 0	5 4	5 2	5 1	4 9	5 3	5 2	5 0	4 9	5 2	5 1	4 9	4 8	5 1	4 9	4 8	4 7	4 6				
			5 . 0	5 5	5 3	5 2	5 1	5 4	5 3	5 1	5 0	5 3	5 2	5 1	5 0	5 1	5 1	5 0	4 9	4 7				
			7 . 0	5 6	5 5	5 4	5 3	5 5	5 4	5 3	5 2	5 4	5 3	5 2	5 1	5 2	5 2	5 1	5 0	4 9				
			1 0 . 0	5 6	5 6	5 5	5 4	5 6	5 5	5 4	5 4	5 4	5 4	5 3	5 3	5 3	5 3	5 2	5 2	5 0				

