

# 屋内照明器具特性

|         |                     |  |  |  |  |           |  |  |  |  |
|---------|---------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | FYY22220            |  |  |  |  |           |  |  |  |  |
| 光源      | LED3500_85_2360 x1  |  |  |  |  | 2360.0 lm |  |  |  |  |
| 管理番号    | K0166073(0)DB1      |  |  |  |  |           |  |  |  |  |
| BZ分類    | BZ5/3.5/BZ6/4.5/BZ5 |  |  |  |  |           |  |  |  |  |

|        |                  |         |                  |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|------------------|---------|------------------|------|------|-----|-----|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%             | 天井      | 80%              |      |      |     | 70% |      |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |     |
|        | 上方光束             |         | 0%               | 反射率  | 70   | 50  | 30  | 10   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
|        | 下方光束             |         | 100%             |      | 床    | 10% |     |      |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     |
| 室指数    | 照明率 ( X0.01 )    |         |                  |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     | ZCM |     |
| 保守率    | 良                | 0.83    | 0.6              | 5.5  | 4.2  | 3.4 | 2.8 | 5.3  | 4.1 | 3.4 | 2.8 | 5.1 | 4.0 | 3.3 | 2.8 | 4.9 | 3.9 | 3.3 | 2.8 | 2.6 |     |
|        | 中                | 0.81    | 0.8              | 6.4  | 5.2  | 4.4 | 3.8 | 6.3  | 5.1 | 4.3 | 3.7 | 6.0 | 5.0 | 4.3 | 3.7 | 5.7 | 4.8 | 4.2 | 3.7 | 3.5 |     |
|        | 否                | 0.77    | 1.0              | 7.1  | 5.9  | 5.1 | 4.4 | 6.9  | 5.8 | 5.0 | 4.4 | 6.6 | 5.6 | 4.9 | 4.4 | 6.3 | 5.5 | 4.9 | 4.4 | 4.1 |     |
|        |                  |         | 1.25             | 7.6  | 6.6  | 5.8 | 5.1 | 7.5  | 6.5 | 5.7 | 5.1 | 7.1 | 6.3 | 5.6 | 5.1 | 6.8 | 6.1 | 5.5 | 5.0 | 4.8 |     |
| 下方投影面積 | c m <sup>2</sup> |         | 1.5              | 8.1  | 7.1  | 6.3 | 5.7 | 7.9  | 7.0 | 6.2 | 5.6 | 7.5 | 6.7 | 6.1 | 5.6 | 7.2 | 6.6 | 6.0 | 5.5 | 5.3 |     |
|        | 等価発光面積           |         | c m <sup>2</sup> | 2.0  | 8.6  | 7.8 | 7.1 | 6.5  | 8.4 | 7.7 | 7.0 | 6.5 | 8.1 | 7.4 | 6.9 | 6.4 | 7.8 | 7.2 | 6.7 | 6.3 | 6.0 |
| 取付高さ   | 器具間隔最大限          |         | 2.5              | 9.0  | 8.3  | 7.6 | 7.1 | 8.8  | 8.1 | 7.5 | 7.0 | 8.5 | 7.9 | 7.4 | 6.9 | 8.2 | 7.7 | 7.2 | 6.9 | 6.6 |     |
|        | 横方向 (A)          | 縦方向 (B) | 3.0              | 9.3  | 8.6  | 8.0 | 7.5 | 9.1  | 8.5 | 7.9 | 7.5 | 8.8 | 8.2 | 7.8 | 7.4 | 8.5 | 8.0 | 7.6 | 7.3 | 7.0 |     |
| 1.5m   | 1.93m            | 1.8m    | 4.0              | 9.6  | 9.1  | 8.6 | 8.2 | 9.4  | 8.9 | 8.5 | 8.1 | 9.1 | 8.7 | 8.3 | 8.0 | 8.8 | 8.5 | 8.2 | 7.9 | 7.6 |     |
| 2      | 2.49             | 2.42    | 5.0              | 9.8  | 9.4  | 9.0 | 8.6 | 9.7  | 9.3 | 8.9 | 8.5 | 9.4 | 9.0 | 8.7 | 8.4 | 9.1 | 8.8 | 8.5 | 8.2 | 8.0 |     |
| 2.5    | 3.05             | 3.01    | 7.0              | 10.1 | 9.7  | 9.4 | 9.1 | 9.9  | 9.6 | 9.3 | 9.1 | 9.6 | 9.4 | 9.1 | 8.9 | 9.4 | 9.2 | 8.9 | 8.7 | 8.4 |     |
| 3      | 3.62             | 3.68    | 10.0             | 10.3 | 10.1 | 9.8 | 9.6 | 10.2 | 9.9 | 9.7 | 9.5 | 9.9 | 9.7 | 9.5 | 9.3 | 9.6 | 9.5 | 9.3 | 9.1 | 8.8 |     |

