

屋内照明器具特性

品番 (品名)	FYY22730				
光源	LED3000_85_910 x1		910.0 lm		
管理番号	K0166072(0)DB1				
BZ分類	BZ6/1.4/BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%					
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
	下方光束		100%		床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																				ZCM			
保守率	良	0.83	0.6	5.2	3.9	3.0	2.4	5.1	3.8	3.0	2.4	4.8	3.7	2.9	2.4	4.6	3.6	2.9	2.4	2.2				
	中	0.81	0.8	6.2	4.9	4.1	3.4	6.1	4.9	4.0	3.4	5.8	4.7	4.0	3.4	5.5	4.6	3.9	3.4	3.2				
	否	0.77	1.0	6.9	5.7	4.9	4.2	6.8	5.6	4.8	4.2	6.4	5.5	4.7	4.2	6.1	5.3	4.7	4.1	3.9				
	下方投影面積	c m ²		1.25	7.6	6.5	5.7	5.0	7.4	6.4	5.6	5.0	7.1	6.2	5.5	5.0	6.8	6.0	5.4	4.9	4.7			
等価発光面積	c m ²		1.5	8.1	7.1	6.3	5.7	7.9	7.0	6.2	5.7	7.5	6.8	6.1	5.6	7.2	6.6	6.0	5.5	5.3				
	c m ²		2.0	8.7	7.9	7.2	6.6	8.5	7.8	7.1	6.6	8.2	7.5	7.0	6.5	7.9	7.3	6.9	6.4	6.2				
取付高さ	器具間隔最大限		2.5	9.1	8.4	7.8	7.3	横方向 (A)		縦方向 (B)		8.9	8.3	7.7	7.2	8.6	8.0	7.6	7.1	8.3	7.8	7.4	7.1	6.8
	0	0						2.01	2.01															
2	0	2.66	5.0	9.9	9.5	9.2	8.8	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.6	9.2	9.0	8.7	8.4	8.1	7.8	7.5	7.2	
2.5	0	3.3	7.0	10.2	9.9	9.6	9.4	10.1	9.8	9.5	9.3	9.8	9.5	9.3	9.1	9.5	9.3	9.1	9.0	8.7	8.4	8.1	7.8	
3	0	3.96	10.0	10.4	10.2	10.0	9.8	10.2	10.0	9.9	9.7	10.0	9.8	9.7	9.5	9.7	9.6	9.5	9.3	9.0	8.7	8.4	8.1	

