

屋内照明器具特性	
品番 (品名)	L G B 8 1 7 0 0
光源	LED5000_70_460 ×1 460.0 l m
管理番号	K0151935 (0) DB 1
B Z 分類	B Z 6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		2 8 %	室指数	照明率 (X 0 . 0 1)																		Z C M		
下方光束		7 2 %																						
保守率		良 中 否	0 . 6 3	0 . 6	0 . 6	0 . 5 6	0 . 6	4 9	3 6	2 8	2 3	4 6	3 5	2 7	2 2	4 1	3 1	2 5	2 0	3 6	2 8	2 3	1 9	1 5
			0 . 6	0 . 8	5 8	4 6	3 8	3 2	5 5	4 4	3 6	3 0	4 9	4 0	3 3	2 8	4 3	3 6	3 0	2 6	2 1			
			1 . 0	6 4	5 3	4 4	3 8	6 1	5 0	4 3	3 7	5 4	4 5	3 9	3 4	4 8	4 1	3 5	3 1	2 6				
			1 . 2 5	7 0	5 9	5 1	4 5	6 6	5 6	4 9	4 3	5 9	5 1	4 5	4 0	5 2	4 6	4 1	3 7	3 0				
下方投影面積		c m ²	1 . 5	7 4	6 4	5 7	5 0	7 0	6 1	5 4	4 8	6 3	5 5	4 9	4 5	5 6	5 0	4 5	4 1	3 4				
等価発光面積			c m ²	2 . 0	8 0	7 1	6 4	5 8	7 6	6 8	6 2	5 6	6 8	6 1	5 6	5 2	6 0	5 5	5 1	4 7	4 0			
2 . 5	8 4			7 6	7 0	6 4	7 9	7 2	6 7	6 2	7 1	6 6	6 1	5 7	6 4	5 9	5 5	5 2	4 4					
取付 高さ	器具間隔最大限		3 . 0	8 6	7 9	7 4	6 9	8 2	7 6	7 1	6 6	7 4	6 9	6 4	6 1	6 6	6 2	5 9	5 5	4 7				
	横方向 (A)		縦方向 (B)		4 . 0	9 0	8 4	7 9	7 5	8 5	8 0	7 6	7 2	7 7	7 3	6 9	6 6	6 6	6 3	6 0	5 1			
H m	1 . 4 6 H m	1 . 4 6 H m	5 . 0	9 2	8 7	8 3	7 9	8 7	8 3	7 9	7 6	7 9	7 6	7 3	7 0	7 1	6 8	6 6	6 4	5 4				
			7 . 0	9 4	9 1	8 7	8 4	9 0	8 7	8 4	8 1	8 2	7 9	7 7	7 4	7 4	7 2	7 0	6 8	5 8				
			1 0 . 0	9 6	9 4	9 1	8 9	9 2	9 0	8 7	8 5	8 4	8 2	8 0	7 8	7 6	7 4	7 3	7 1	6 1				

