

| | |
|----------|------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | XLX450CEWT |
| 光源 | LED4000_85_4780 x1 4780.0 lm |
| 管理番号 | K0132113 (6) DB1 |
| BZ分類 | BZ6 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|-------------------------------------|---------|-------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 17% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 83% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 中 否 0.83 0.81 0.77 | 0.6 | 51 | 38 | 30 | 24 | 49 | 37 | 29 | 24 | 45 | 34 | 28 | 23 | 41 | 32 | 26 | 22 | 19 | |
| | | 0.8 | 60 | 48 | 39 | 33 | 57 | 46 | 38 | 32 | 53 | 43 | 36 | 31 | 48 | 40 | 34 | 30 | 26 | |
| | | 1.0 | 66 | 55 | 46 | 40 | 63 | 53 | 45 | 39 | 58 | 49 | 42 | 37 | 53 | 46 | 40 | 35 | 31 | |
| | | 1.25 | 72 | 61 | 53 | 47 | 69 | 59 | 51 | 45 | 63 | 55 | 48 | 43 | 58 | 51 | 46 | 41 | 36 | |
| 下方投影面積 | cm ² | 1.5 | 76 | 66 | 58 | 52 | 73 | 64 | 56 | 51 | 67 | 59 | 53 | 48 | 62 | 55 | 50 | 46 | 40 | |
| | | 2.0 | 82 | 73 | 66 | 60 | 79 | 71 | 64 | 58 | 72 | 66 | 60 | 55 | 67 | 61 | 57 | 53 | 47 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 86 | 78 | 71 | 66 | 82 | 75 | 69 | 64 | 76 | 70 | 65 | 61 | 70 | 65 | 61 | 57 | 51 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 88 | 81 | 75 | 70 | 85 | 79 | 73 | 68 | 78 | 73 | 69 | 65 | 73 | 68 | 65 | 61 | 55 |
| 1.5m | 1.98m | 2.16m | 4.0 | 92 | 86 | 81 | 76 | 88 | 83 | 78 | 74 | 82 | 78 | 74 | 70 | 76 | 73 | 69 | 66 | 60 |
| 2 | 2.61 | 2.71 | 5.0 | 94 | 89 | 85 | 81 | 90 | 86 | 82 | 78 | 84 | 81 | 77 | 74 | 78 | 75 | 72 | 70 | 63 |
| 2.5 | 3.24 | 3.3 | 7.0 | 96 | 93 | 89 | 86 | 93 | 90 | 86 | 83 | 87 | 84 | 81 | 79 | 81 | 79 | 76 | 74 | 67 |
| 3 | 3.87 | 3.89 | 10.0 | 99 | 96 | 93 | 90 | 95 | 93 | 90 | 88 | 89 | 87 | 85 | 83 | 83 | 82 | 80 | 78 | 71 |

